

EM4000SX	EM5000SX		EM5000 <i>i</i> s	EM6500SX	SPECIFICATIONS
Honda iGX270	Honda iGX390		Honda GX340	Honda iGX390	Engine
Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled		Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	
270cc	389cc		337cc	389cc	Displacement
120/240V 4000W max. (33.3/16.7A) 3600W rated (30/15A)	120/240V 5000W max. (41.2/20.8A) 4500W rated (37.5/18.6A)		120/240V 5000W max. (41.7/20.8A) 4500W rated (37.5/18.8A)	120/240V 6500W max. (54.2/27.1A) 5500W rated (45.8/22.9A)	AC output
5000W (41.7/20.8A) for 10 sec.	7000W (58.3/29.2A) for 10 sec.		N/A	7000W (58.3/29.2A) for 10 sec.	iAVR AC output
C(2), F, G	C(2), F, H		C, F, H	C(2), F, H	Receptacles
12V, 100W (8.3A)	12V, 100W (8.3A)		N/A	12V, 100W (8.3A)	DC output
Recoil, electric	Recoil, electric		Recoil, electric	Recoil, electric	Starting system
6.2 gal.	6.2 gal.		4.5 gal.	6.2 gal.	Fuel tank capacity
10.1 hrs.@ rated load, 16.0 hrs. @ 1/2 load	8.1 hrs. @ rated load, 11.2 hrs. @ 1/2 load		5.7 hrs.@ rated load, 15.2 hrs. @ 1/4 load	6.9 hrs. @ rated load, 10.4 hrs. @ 1/2 load	Run time per tankful
41.1" x 27.8" x 30.4"	41.1" x 27.8" x 30.5"		31.9" x 26.4" x 27.2"	41.1" x 27.8" x 30.6"	Dimensions (L x W x H)
71 dB @ Rated Load 97 LwA ⁺⁺	72 dB @ rated load 99 LwA ⁺⁺		68 dB(A) @ rated load, 62 dB(A) @ 1∕4 load 98 LwA [↑]	73 dB @ rated load 100 LwA ⁺⁺	Noise level
201 lbs.	232 lbs.		217 lbs.	243 lbs.	Dry weight
EM4000SX	EM5000SX		EM5000 <i>i</i> s	EM6500SX	FEATURES
•	•		•	•	Honda OHV engine
•	•		•	•	Electric start/Remote start option
•	•		•	•	Oil Alert*
•	•			•	Auto Throttle®
			•		Eco-Throttle [™] (load dependent operation)
•	•		•	•	Electronic ignition
•	•			•	Simultaneous AC/DC use
•	•		Electronic	•	Circuit breakers
•	•		•	•	Fuel gauge
			•		<i>i</i> -Wonitor
•	•		•	•	Wheel kit standard
•	•			•	iAVR
•	•			•	DAVR
					CycloConverter**
			•		Inverter
					One switch for engine/fuel valve on/off
•	•			•	Full tubing frame for protection
•	•		•	•	USDA-qualified spark arrester/muffler
					Fully enclosed for quieter operation
•	•		•	•	120/240V selector switch
3 Years	3 Years		3 Years	3 Years	GFCI/neutral bond Residential warranty
3 Years	3 Years		3 Years 3 Years	3 Years	Commercial warranty
RECEPTACLE DESCRIPTION	PLUG# RECEPTACLE DESCRIPTION		PLUG#	o idais	Commercial Waltany
F 30A 125V Locking Plug L5-30P H 30A 125/250V Locking G 20A 125/250V Locking Plug L14-20P I 50A 125/250V Locking Plug L14-20P			g Plug CS6365		
J 20A 125V Single 5-20P					