

DISTRIBUTOR NET PRICES FOR 60 HERTZ, 1800 RPM UL-142 Certified Dual Wall Diesel Sub-Base Tank FOR "LEAK-PROOF" OPERATION ON 15 - 350 KW GENERATOR SETS FOR SPJD & SPMD SERIES

GEN-SET MODEL	DOUBLE WALL FUEL TANK MODEL	AVERAGE GPH FUEL CONSUMPTION			AVERAGE FULL TANK RUN HOURS			TANK CAPACITY		(3) EMERGENCY VENTS	SKID BASE & HOUSING LENGTH INCHES	FUEL TANK DIMENSIONS			SHIP WT. (LBS)	
		50% LOAD	75% LOAD	100% LOAD	50% LOAD	75% LOAD	100% LOAD	GAL.	LTR.			LG. IN.	WI. IN.	HI. IN.		
SPJD-250	S-48	1.0	1.5	2.0	48	32	24	48	182	2"	68" BASE & 82" HOUSING	102	36	10	480	
	S-96				96	64	48	96	364	3"		102	36	14	570	
	S-145				145	96	72	144	545	3"		102	36	19	680	
SPJD-300	S-67	1.4	2.1	2.8	48	32	24	67	254	2"		102	36	11	510	
	S-134				96	64	48	134	508	3"		102	36	19	680	
	S-202				144	96	72	202	765	3"		102	36	26	857	
SPJD-420	S-84	1.75	2.6	3.5	48	32	24	84	318	3"		78" BASE & 94" HOUSING	114	42	10	600
	S-168				96	64	48	168	636	3"			114	42	16	750
	S-252				144	96	72	252	954	3"			114	42	24	981
SPJD-520	S-94	1.95	2.9	3.9	48	32	24	94	356	3"	114		42	10.5	600	
	S-187				96	64	48	187	818	3"	114		42	18	800	
	S-281				144	96	72	281	1064	4"	114		42	26	1031	
SPJD-600	S-108	2.3	3.4	4.5	48	32	24	108	409	3"	114		42	11	630	
	S-216				96	64	48	216	818	3"	114		42	21	905	
	S-324				144	96	72	324	1226	4"	114		42	31	1157	
SPJD-800	S-144	3.0	4.5	6.0	48	32	24	144	564	3"	98" BASE & 122" HOUSING	142	48	10	830	
	S-288				96	64	48	288	1128	4"		142	48	18	1123	
	S-446				144	96	72	446	1688	4"		142	48	26	1379	
SPJD-1000	S-170	3.6	5.4	7.1	48	32	24	170	644	3"		142	48	11	860	
	S-341				96	64	48	341	1291	4"		142	48	21	1219	
	S-511				144	96	72	511	1934	4"		148	48	30	1507	
SPJD-1250	S-206	4.3	6.6	8.6	48	32	24	206	780	3"		110" BASE & 134" HOUSING	154	48	12	1010
	S-413				96	64	48	413	1563	4"			154	48	23	1354
	S-619				144	96	72	619	2343	5"			165	48	30	1698
SPJD-1550	S-266	5.5	8.3	11.1	48	32	24	266	1007	4"	154		48	15	1113	
	S-533				96	64	48	533	2017	4"	154		48	28	1560	
	S-799				144	96	72	799	3024	5"	200		48	30	2245	
SPJD-1800	S-300	6.3	9.4	12.5	48	32	24	300	1136	4"	154		48	17	1182	
	S-600				96	64	48	600	2271	4"	160		48	30	1698	
	S-900				144	96	72	900	3407	5"	225		48	30	2245	
SPJD-2100	S-353	7.4	11.0	14.7	48	32	24	353	1336	4"	154	48	20	1285		
	S-716				96	64	48	716	2710	5"	185	48	30	1895		
	S-1059				144	96	72	1059	4008	5"	255	48	30	2570		
SPMD-2500	S-430	10.5	14.4	17.8	48	32	24	430	1628	4"	132" BASE & 162" HOUSING	175	52	22	1933	
	S-860				96	64	48	860	3255	5"		175	52	38	3150	
	S-1290				144	96	72	1290	4883	5"		194	52	48	4193	
SPMD-2800	S-470	11.6	15.1	19.5	48	32	24	470	1779	4"		175	52	21	1983	
	S-940				96	64	48	940	3596	5"		175	52	41	3325	
	S-1405				144	96	72	1405	5337	6"		210	52	48	4465	
SPMD-3000	S-490	12.1	15.9	20.4	48	32	24	490	1855	4"		175	52	22	2033	
	S-980				96	64	48	980	3710	5"		175	52	43	3441	
	S-1470				144	96	72	1470	5565	6"		216	52	48	4633	
SPMD-3500	S-575	14.1	17.8	23.8	48	32	24	575	2177	5"	148" BASE & 184" HOUSING	196	60	20	2413	
	S-1145				96	64	48	1145	4334	5"		196	60	38	3836	
	S-1715				144	96	72	1715	6492	6"		214	60	48	4912	
SPMD-4000	S-655	16.5	20.8	27.2	48	32	24	655	2479	5"		196	60	23	2590	
	S-1310				96	64	48	1310	4959	5"		196	60	43	4179	
	S-1960				144	96	72	1960	7419	6"		236	60	48	5390	

CAUTION: CONSULT YOUR LOCAL FIRE CODES FOR FUEL STORAGE. MANY STATES HAVE SPECIFIC AND DIFFERENT FUEL TANK REQUIREMENTS. CONSULT YOUR LOCAL FIRE DEPARTMENT FOR COMPLIANCE WITH POSSIBLE SPECIAL TANK INSTALLATIONS.