

Redesigned Honda **WB20XT3** & **WB30XT3** General Purpose De-Watering Pumps

**Brand New!
From Honda!**



WB30XT3



FEATURES/BENEFITS

- Honda commercial grade GX Series engine
- Increased efficiency with redesigned impeller and volute
- New styling (fuel tank & frame design)*
- Easier carburetor access thanks to the WB30XT's redesigned frame
- WB30XT housing size reduction requires less water when priming
- 100% Honda designed
- 3-Year Limited Warranty



WB20XT3

SPECIFICATIONS

	WB20XT3	WB30XT3
Engine	Honda GX120	Honda GX160
Displacement	118cc	163cc
Bore and Stroke	2.4" x 1.7"	2.7" x 1.8"
Compression Ratio	8.5:1	9.0:1
Pump Type	Centrifugal, Self-priming	Centrifugal, Self-priming
Volute	Rigid Mounted Cast Iron	Rigid Mounted Cast Iron
Impeller	4 Vane Cast Iron	4 Vane Cast Iron
Priming Time	110 sec. @ 16.4 ft.	150 sec. @16.4 ft.
Discharge Capacity	164 gal./min.	290 gal./min.
Suction Port Diameter	2" NPT	3" NPT
Total Head Lift	105 ft.	85 ft.
Suction Head Lift	25 ft.	25 ft.
Maximum Pressure	45 psi	37 psi
Dimensions (LxWxH)	19.3" x 14.4" x 16.5"	20.1" x 15.2" x 17.9"
Dry Weight	44 lb.	57 lb.
3-Year Limited Warranty	Standard	Standard



HONDA PUMPS

pumps.honda.com



*Frame design styling applies to WB30XT3 only.

For optimum performance and safety we recommend you read the owner's manual before operating your Honda Power Equipment. Specifications subject to change without notice. ©2014 American Honda Motor Co., Inc.