

WINGCO®

Quality Generators Since 1927

WC10000VE



Engine:

- Briggs and Stratton Vanguard
- CARB & EPA certified
- V-Twin OHV
- Cast iron sleeves
- Commercial grade engine
- 3 year commercial warranty is included standard
- Designed to deliver the dependability you need to get a lot more done in less time, and at less cost throughout the workday

Generator End:

- 100% copper windings - longer life and improved motor starting
- Dampers, skewed rotors for <6% harmonic distortion
- 425 Volt heavy duty capacitors
- 25 Amp 1200 volt diodes
- Varistors provide an extra layer of protection for the rotor diodes by intervening at 360 VAC and 470 VDC

Components:

- 7 gallon steel fuel tank
- Heavy duty 1 1/4 inch 13 gauge tubular steel cradle
- Powder coat paint on steel components for an incredibly durable finish
- Optional 2 wheel industrial dolly kit with fold down handle
- Solid full width steel axles
- Standard lifting eye
- Electric / recoil start
- Generous receptacle package
- Square D circuit breaker- Industry's leading trip reaction time at 1/60th of a second
- Industry's only trip indicator system (Red-Visi Trip)
- All receptacles GFCI protected except the 60 AMP 120/240 volt, this 14-60 receptacle is compatible with building distribution panels
- NEMA 5-20 GFCI receptacles fitted with UL listed metal covers for protection against the elements
- Battery not included, battery required for electric start: 12V BCI group U1 rated 275 CCA or larger



Big Dog Series

SURGE WATTS	10500
CONTINUOUS WATTS	9600
AMPS	40/80
VOLTS	120/240
VOLTAGE REGULATION	+/-5%
FREQUENCY REGULATION	+/-3%
ENGINE BRAND	B & S VANGUARD
ENGINE MODEL	MODEL 35
ENGINE STARTER	ELECTRIC/RECOIL
ENGINE SPEED	3600 RPM
DISPLACEMENT	570 CC
ENGINE CYLINDERS	V-TWIN
LOW OIL PROTECTION	STANDARD
dBA AT 7 METERS	78
FUEL TANK	7
FULL LOAD RUN TIME	4.3 HRS
FUEL USE (GAL/HR)	1.6 GAL/HR
FULL PRESSURE OIL LUBE WITH SPIN-ON FILTER	STANDARD
MOTOR STARTING (CODE G)	5 HP
2 WHEEL DOLLY KIT	OPTIONAL
MAIN CIRCUIT BREAKER	40 AMP / 240 VOLT
HOUR METER	STANDARD
120 VOLT RECEPTACLES	(4) NEMA 5-20R 20 AMP (GFCI)
120/240 VOLT RECEPTACLE	(1) NEMA 14-60R 60 AMP
240 VOLT RECEPTACLE	(1) NEMA L6-30R 30AMP (GFCI)
DIMENSIONS (LxWxH)	33.7" x 28" x 22.1"
DIMENSIONS W/WHEEL KIT	38.3" x 28.8" x 28.9"
NET WEIGHT	251 LBS
SHIP WEIGHT	276 LBS
WARRANTY (ENG/GEN)	3 YRS / 2 YRS

Presented by:

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057