



## WL12000HE

### Engine:

- Honda GX630
- Honda V-twin engines offer higher horsepower, improved adaptability, quiet operation, and greater fuel efficiency. A 3 year commercial warranty comes standard.
- CARB & EPA certified engine
- V Twin OHV
- Cast Iron Sleeves
- Commercial Grade Engines

### Generator End:

- 100% copper windings - longer life and improved motor starting.
- Dampers, skewed rotors for < 5% harmonic distortion.
- 425 Volt heavy duty capacitors
- 25 Amp 1200 Volt diodes
- Varistors provide an extra layer of protection for the rotor diodes by intervening at 360 VAC and 470 VDC

### Components:

- 15 gallon corrosion free fuel tank
- Heavy duty 1 ¼ inch 13 gauge tubular steel cradle.
- Industrial DuPont powder coated paint on industrial grade galvanized steel for an incredibly durable finish.
- 4 wheel dolly kit standard
- Solid steel axles
- Standard lifting eye
- Electric Start
- Generous receptacle package
- Square D Circuit Breakers- Industry's leading trip reaction time at 1/60th of a second.
- Industry's only trip indicator system (Red-Visi Trip)

SURGE WATTS	12000
CONTINUOUS WATTS	10800
AMPS	90/45
GENERATOR REGULATION	5%
FREQUENCY REGULATION	5%
ENGINE BRAND	HONDA
ENGINE MODELS	GX630 OHV
ENGINE STARTER	ELECTRIC
ENG. HP/3600 RPM	3600
DISPLACEMENT	688 C.C.
ENGINE CYLINDERS	V-TWIN
LOW OIL PROTECTION	STANDARD
DB(A) AT 7 METERS	78
FUEL TANK (GAL.)	15
FULL LOAD RUN TIME (HRS.)	9 HOURS
FUEL USE (GAL/HR)	1.3
FULL PRESSURE OIL LUBE WITH SPIN-ON FILTER	INCLUDED
CODE G, ELECTRIC MOTOR STARTING POWER	6 HP
BUILT-IN 4 WHEEL DOLLY	YES
MAIN CIRCUIT BREAKER	45 AMP, 240V
HOURLY METER	INCLUDED
120 VOLT RECEPTACLES	(4) NEMA 5-20R (GFCI)
	(1) NEMA L5-20R 20AMP
120/240 VOLT RECEPTACLE	(1) NEMA 14-60R 60AMP
240 VOLT RECEPTACLE	(1) NEMA L6-30R 30AMP
DIMENSIONS LxHxW	39.5 x 26.5 x 26
NET WEIGHT (LBS.)	487
SHIP WEIGHT (LBS.)	412
WARRANTY (ENG/GEN)	3yr / 2yr

