# PE-4013HPWSCOMZ-HWTB

## HONDA GX390, 4000 PSI

POWERED by HONDA

## SPECIFICATIONS

STAINLESS STEEL FRAME

| PART# | GPM | PSI | DISPLACEMENT | TRIPLEX PUMP | UNLOADER |
|---|---|---|---|---|---|
| PE-4013HWPSCOMZ-HWTB | 4.0 | 4000 | 389cc HONDA GX390 | COMET ZWD4040G | EXTERNAL |

### ACCESSORIES INCLUDED

| PART # | DESCRIPTION |
|---|---|
| 2 x 85.238.153 | 3/8" 50' HIGH PRESSURE STEEL BRAIDED HOSE |
| 85.205.026 | WAND ASSEMBLY WITH GUN AND COUPLER |
| 85.210.040BEP | #4 QUICK CONNECT NOZZLES: 0°,15°, 40°, SOAPER |
| 85.206.018L | 18" STANDARD FIBERGLASS TELESCOPING WAND |
| 85.403.007 | 20" WHIRL-A-WAY |
| 85.300.044 | BALL VALVE KIT |

### ADDITIONAL INFO

- LOW PRESSURE CHEMICAL INJECTOR
- STAINLESS STEEL FRAME **PART# 85.600.078**
- 13" PNEUMATIC TIRES **PART# 85.660.036**
- ENGINE OIL 10W 30 **PART# 85.490.002**
- PUMP OIL 30W NON DETERGENT **PART# 85.490.000**
- 1" KEYED SHAFT

### PUMP OPTIONS

**COMET ZWD4040G**
85.149.022B
**PUMP REBUILD KIT**
73.149.022
**REPLACEMENT UNLOADER**
85.300.037

### SHIPPING



ENGINE WARRANTY

PUMP WARRANTY