

8 GALLON GAS POWERED TWIN TANK WHEELBARROW COMPRESSOR

DXCMH1608WB



pump performance helps to ensure trouble-free operation

10" Foam Filled Tire

manuverability over rough terrain, and job-sites

Controls vibration and helps to prevent crawling

GUARANTEED TOUGH.

draining

DXCMH1608WB 8 GALLON GAS POWERED TWIN TANK WHEELBARROW COMPRESSOR



PERFORMANCE		EASE OF USE			SPECIFICATIONS *Tested Per ISO 1217	
		On Deevel	Currentier		Catalog Number	DXCMH1608WB
	150 Max PSI	On-Board Controls	Superior Mobility	Ball Drain Valve	Horsepower (HP) Continuous*	5.5
	5.5 нр	UUIIUIUI	mobility	Valve	Control	Start/Stop
					Drive	Belt
	Continuous	DURABILITY			Tank (Gallon/Liter)	8
	Motor per IS01217			ı, Twin Cylinder	Power Supply	Honda - GX160 Gas Belt Drive
	8.0		ANA Metal Be		SCFM @ 100 PSI*	9.0
	Gallon Tank			ertified Tank	Framers Recommended	7.0
					Roofers Recommended	4-7
	9.0 SCFM per IS01217			elt Guard	Pump Speed (RPM)	925
					Tool Length (Inches)	44.27
				Mount Foam-Filled	Tool Width (Inches)	18.25
					Tool Height (Inches)	25.15
RELIABILITY		200			Tool Weight (lbs.)	165

S.5 HP Honda GX160 Engine

Oil-lubed, Long-Life Pump

> 1-888-895-4549 dewalt.com



DEALER STAMP

The following are examples of trademarks for one or more DEWALT Power Tools and Accessories: The yellow and black scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool. Copyright ©2011 MAT Industries, LLC, Long Grove, IL. Under license from DEWALT Industrial Tool Co.