

# EASY-KLEEN

**PRESSURE SYSTEMS LTD.**

MANUFACTURER OF HIGH PRESSURE CLEANING EQUIPMENT

**Commercial Hot Water Electric**



**EZO1520E**

**EZO3636E**



**MADE IN CANADA** 

**HARD WORKING, RELIABLE & EFFICIENT.**

[www.easykleen.com](http://www.easykleen.com)

**1-800-315-5533**

Email: [sales@easykleen.com](mailto:sales@easykleen.com)

# EASY-KLEEN

**PRESSURE SYSTEMS LTD. MADE IN CANADA\***

**MANUFACTURER OF HIGH PRESSURE CLEANING EQUIPMENT**

**Commercial Oil, Propane & Natural Gas Fired Electric Motor Driven Series**

## Standard Features

<b>PUMP</b>	Commercial Duty triplex plunger pump with oil bath crankcase, stainless valves and all brass manifolds, direct drive 1750 rpm on all models c/w thermo protection
<b>MOTOR</b>	Farm Duty full 1.15 service factor TEFC manual reset overload protected motor
<b>OTHER</b>	Fully adjustable pressure regulator, temperature controller, 50 ft hose, gun and wand with five nozzles
<b>HEATING COIL</b>	Heating Coil, elliptically wound cold process of stretched reduced full body normalized ASTM A53/APIPSL schedule 80 pipe, and is structurally braced to minimize pipe wear and vibration, all completely sealed with ceramic blanket with stainless steel coil skin for total efficiency. You will save time and money on heat up time and fuel every time you use an Easy Kleen hot water cleaning systems
<b>BURNERS</b>	Quality North American made Oil fired burners or Gas fired burner controls with adjustable thermostats are used for efficiency, dependability and serviceability. Is equipped with a cleanable fuel filter
<b>ELECTRICAL CONTROL PANEL</b>	Electrical Nema 4 water tight control panel with easy access, heavy duty on/off cam switch standard or optional auto stop/start with time delay shut down all mounted in a hinged Nema 4 control panel with quality components
<b>FRAME</b>	Rugged 12 gauge bent one piece steel frame all welded with lifting bar and roll cage frame all powder coated and housing a 10 gallon poly fuel tank. A hose reel can be mounted on the front plate. 3/4" axles are welded to frame and 13" pneumatic wheels are held on with 3/4" nuts or stationary (ST).

MODEL	GPM	PSI	HP	ELECTRIC DRIVE
EZO1520E	2	1500	2/110V/1ph	1750 RPM
EZO2434E	3.4	2400	5/220V/1ph	1750 RPM
EZO2530E-GP	3	2500	5/220V/1ph	1750 RPM
EZO3636E	3.6	3600	7.5/220V/1ph	1750 RPM
EZO3630E-GP	3	3600	7.5/220V/1ph	1750 RPM

\*PROPANE FIRED USE EZP—NATURAL GAS FIRED USE EZN & ADD \$550

## Call 1-800-315-5533

[www.easykleen.com](http://www.easykleen.com)

[sales@easykleen.com](mailto:sales@easykleen.com)

You will be proud of your NEW Easy Kleen pressure washer now and for years to come.

## HARD WORKING, RELIABLE & EFFICIENT