



## 15hp -20hp Standard Drive Complete Rotary Air System







Our Rotary screws are the most energy efficient with our soft start by limiting the voltage upon start up









breakers UL/CSA listed

Mann Filters

VMC inlet valve and load Solenoid

- Schneider y Delta magnetic contactors UL/CSA listed
- VMC inlet valve and load solenoid
- \*10 Year warranty on airend- 5 year on the cabinet and components



PLC Controller monitors maintenance, temp ,oil level, filtration, hours, plus remote start/stop, timed start/stop automatic restart



Patented swing arm mount for quick and easy maintenance, simply take out the pin and swing the dryer to the side accessing the door panel.

Making the unit more compact taking up less space!

taking up less space!		
	ERSK150003	ERSK200003
Running HP	15	20
CFM 100PSI	70	86
MAX PSI	145	145
<b>Drive Type</b>	Belt	Belt
Tank Size	120 Gal	120 Gal
Airend Model	Rotocomp-EVO03	Rotocomp-EVO03
Dryer CFM	115 CFM	115 CFM
Outlet size	1"	1"
<b>Motor Phase</b>	Three	Three
Dimensions	71" x 27" x 70"	71" x 27" x 70"
Weight	1315	1315
Product Source	USA, Germany, Italy	USA, Germany, Italy

\*10 year warranty is only valid with annual purchase of service kit



