


PREMIUM INDUSTRIAL GAS POWERED

Energy efficiency & MAX imum performance

Engineered & Tested In The USA

GAS POWERED SERIES

• Quiet, low RPM Solid Cast Iron construction for extended life up to 50,000 hours*



 All Steel Rebuildable Connecting Rods with Disc Valves for easy maintenance & long durability



• Flow-Tek™ Concentric Disc Valves for Maximum Performance & Longevity



 Electric Start standard on all models

Contact:



www.EmaxCompressor.com 1000 Cass Drive Clayton, Ohio 45315 Toll Free: 866-294-4153 Fax: 937-540-1157





Features & Benefits

- Cool-Tek: The coolest running compressors in the industry 35% lower operating temperature reduces moisture build up & extends pump life
- · Belt Tension Adjuster: Fast, easy "one turn" way to tighten belts which reduces vibration and extends belt life





1 / -	N. L. usala a.
IVIOGEI	Number

duces vibration and extends belt life						
	o,	TML 33	30	o' 2605	1805	
Ma alal Nicusala au	tistis ben	TWI LEEF 1330	£6£518305	EGES 1860S	ESES AROST	
Model Number	V.	V	~	V	V	
Running HP	8	13	18	18	24	
SCFM	18	24	34	34	52	
Engine RPM	3200	3200	3200	3200	3200	
Electric Start	YES	YES	YES	YES	YES	
Tank Size (Gallons)	17	30	30	60	80	
Maximum PSI	150	175	175	175	175	
Pump Model	APP2V0732S	APP3Y0732T	APP4V1043T	APP4V1043T	APP3Y2062T	
Outlet	NPT 3/4"	NPT 3/4"	NPT 3/4"	NPT 3/4"	NPT 1"	
Weight (lbs)	275	395	540	610	870	
Pump RPM	650	820	800	800	640	
Dimensions: LxWxH	46" x 21" x 37"	51" x 23" x 40"	44" x 23" x 44"	51" x 23" x 50"	72" x 25" x 50"	
Fuel Tank (Capacity)	1 Gal	1 Gal	5 Gal	5 Gal	5 Gal	

^{*} Based on B-10 Bearing Rating







