



TWO STAGE
Solid CAST IRON piston pumps

Since 1977

Energy efficiency & MAXimum performance

PISTON SERIES PUMPS

- Quiet, low RPM Solid Cast Iron construction for extended life - up to 50,000 hours*



Ram-Tek: Solid Steel, heavy gauge rods for maximum performance & durability



Easily accessible, concentric disc valves insure trouble free maintenance and durability



Industrial Grade Tapered Roller Bearings for maximum performance and extended pump life

Contact:



www.EmaxCompressor.com
1000 Cass Drive
Clayton, Ohio 45315
Toll Free: 866-294-4153
Fax: 937-540-1150
sales@emaxcompressor.com



Built in
HEAD UNLOADERS
for continuous
run applications



APP4V2598T

APP3Y1544T

APP4V1043T



Oil Level Sight Glass



Engineered & Tested
In The USA

Features & Benefits

- **Cool-Tek:** The coolest running compressor pumps in the industry – 35% lower operating temperature reduces moisture build up & extends pump life
- **Flow-Tek:** Concentric Disc Valves deliver maximum air flow and reliability with low replacement costs

Model	APP4V1043T	APP3Y1544T	APP4V2598T
CFM Displacement	43	44	98
CFM @ 100 PSI	34	35	91
Maximum PSI	175	175	175
Pump RPM	600	640	710
Noise DB(A)	75	75	79
Bolt Pattern	9 1/4" x 9 1/4"	13 1/2" x 6 3/4"	13 5/8" x 12 5/8"
Belt Type	B	B	B
Belt Number	2	3	4
Outlet	NPT 3/4"	NPT 1-1/4"	NPT 1-1/4"
Weight (lbs.)	282	321	684
Dimensions: LxWxH	28" x 21" x 21"	27" x 14" x 27"	38" x 29" x 26"

* Based on B-10 Bearing Rating

2 YR - Limited warranty on oil-lubricated pumps sold separately



PIXPUMPS02 07/2010