1 of 2

Belt-Drive Power Washer



Power Washers

3800 psi - Model 006712-0 (49-State & Canada) UPC: 696471067125







FEATURES

POWER

 Powerful Generac® OHV Engine delivers maximum cleaning performance and reliability. Low-oil shutdown protects the engine.

DURABLILITY

- Heavy Duty Belt Drive Triplex Pump Up to 3X longer life than direct drive triplex pumps, oil-level sight glass, re-buildable for easy maintenance.
- Steel Reinforced Hose Durable, non-marring hose will not leave scuff marks.

EASE OF USE

Brass Quick Change Fittings - For faster connections.

MOBILITY

- Compact Lightweight Design Up to 50 lbs. less weight vs. other belt-drive power washers.
- Oversized Pneumatic Wheels Easily handle rugged jobsite terrain.

COMFORT

 Ergonomic Spray Gun - Quick change connections, stabilizing side handle, molded grip, and easier-topull trigger for comfort during prolonged use.





3800 psi specifications

PRESSURE AND FLOW

| Outlet Pressure (psi/bar) | 3800/262 |
|---------------------------|----------|
| Flow Rate (gpm)/(L/min) | 3.2/12.1 |

ENGINE

| Manufacturer | Generac |
|-------------------------|----------------------|
| Displacement (in³/cc) | 18.4/302 |
| Туре | OHV (Overhead Valve) |
| Orientation | Horizontal |
| Low Oil Shutdown System | Yes |
| Fuel Capacity (gal/L) | 1.7/6.4 |
| Fuel On/Off Valve | Yes |
| Engine On/Off Switch | Yes |
| Oil Capacity (oz/L) | 37/1.1 |
| Recommended Engine Oil | SAE 30 or 10W30 |
| Throttle Control | Manual |
| Choke | Manual |
| Starting Method | Manual/Recoil |

PUMP

| Туре | Triplex |
|---|--------------------------------|
| Plunger | Ceramic-coated Stainless Steel |
| Maximum Water Supply Temperature (°F/°C) | 100/38 |

HOSE

| Length (ft/m) | 50/15.2 |
|------------------|--------------|
| Rating (psi/bar) | 4000/276 |
| Connectors | Quick Change |

NOZZLES & DETERGENT

| Number of Nozzles per Unit | 5 |
|----------------------------|---------------------|
| Nozzle Descriptions | 0, 15, 25, 40, soap |

GUN & LANCE

| Gun | Professional |
|----------------------------|--------------|
| Gun to Lance Connection | M22 Threaded |
| Gun to Hose Connection | Quick Change |
| Lance Length (in/cm) | 33/84.8 |
| Lance to Nozzle Connection | Quick change |

FRAME & MISC.

| Frame Construction | Steel |
|--------------------|--------------------------------|
| Wheels (in/cm) | 4 x 10 / 10.1 x 25.4 Pneumatic |

DIMENSIONS & WEIGHTS

| Unit Length (in/cm) | 35.5/90.2 |
|------------------------------------|------------|
| Unit Width (wheel to wheel, in/cm) | 25.25/53.3 |
| Unit Height (in/cm) | 26.75/67.9 |
| Unit Weight (lb/kg) | 134/60.8 |
| Boxed Weight (lb/kg) | 185/83.9 |
| Boxed Length (in/cm) | 37.5/82.5 |
| Boxed Width (in/cm) | 27/68.5 |
| Boxed Height (in/cm) | 32/81 |

WARRANTY

