

Ingersoll Rand

Refrigerated Dryers
(7 cfm - 212 cfm)



Reliable, Clean, Dry Air.

Ingersoll Rand

Minimize life cycle costs with an efficient, reliable and environmentally sound solution for cleaner, drier air.

Designed for Worry-free Air Quality

Ingersoll Rand Refrigerated Dryers make providing continuous dry air as easy as piping a self-contained unit into your compressed air supply line.

Corrosion-resistant heat exchangers, an enhanced control-system and high-efficiency moisture-separation ensure a steady long-term supply of dry air. This virtually eliminates cost due to ruined product finishes, scrapped materials or replacement of pneumatic tools and manufacturing equipment destroyed by wet air.

These small-footprint units provide complete, affordable solutions for applications ranging from dry cleaning to auto body shops, to light processing and manufacturing applications. And easy accessibility simplifies routine maintenance.

Designed for Optimum Efficiency

Our dryers offer multiple design features to ensure a constant dew point at all load levels, and to deliver continuous dry-air performance that satisfies ISO7183 and CAGI ADF100 industry standards. The dryer's full function control with enhanced control parameters, diagnostics and alarms is more sophisticated and powerful than similarly sized competitive products. We also test every unit to ensure leak-free operation and compliance with operating specifications.

Standard and High Temperature Models

Standard units are rated for 115°F (46°C) ambient air conditions and are suited for most applications. High-temperature models accommodate inlet air temperatures up to 200°F (94°C) and are ideal for use with compressors that do not include built-in aftercoolers.



Progress is *greener* with Ingersoll Rand

Lowest Cost of Ownership

Ingersoll Rand's refrigerated dryers offer design features that reduce energy consumption and improve reliability:

- 1** Corrosion-resistant heat exchangers reduce air flow restrictions, providing more efficient throughput with less wasted energy. A built-in stainless steel demister efficiently removes all moisture.
- 2** Microprocessor control with an easy-to-use graphic interface lets you adjust and manage system parameters easily and efficiently.
- 3** Variable-speed fans reduce power consumption when units operate at less than maximum cooling capacity, while ensuring a consistent dew point.
- 4** Reliable, fully hermetic compressors use environmentally friendly R134A refrigerant.
- 5** A fully adjustable programmable electronic drain valve helps minimize air loss.



Performance Specifications

Model	Air Flow Rate		Nominal Power Consumption	Voltage	Air Connections	Dimensions			Maximum Inlet Temperature	Weight
	m ³ /hr	scfm				kW	V/Ph/Hz	NPT		
Standard										
D12IN	12	7	0.16	115/1/60	1/2"	12.0 (305)	16.0 (390)	16.0 (408)	140 (60)	40 (18)
D18IN	18	11	0.16	115/1/60	1/2"	12.0 (305)	16.0 (390)	16.0 (408)	140 (60)	40 (18)
D25IN	25	15	0.16	115/1/60	1/2"	12.0 (305)	16.0 (390)	16.0 (408)	140 (60)	40 (18)
D42IN	42	25	0.21	115/1/60	1/2"	16.0 (390)	18.0 (452)	18.0 (453)	140 (60)	60 (27)
D54IN	54	32	0.37	115/1/60	1/2"	16.0 (390)	18.0 (452)	18.0 (453)	140 (60)	62 (28)
D72IN	72	42	0.37	115/1/60	1/2"	16.0 (390)	18.0 (452)	18.0 (453)	140 (60)	62 (28)
D108IN	108	64	0.48	115/1/60	1/2"	16.5 (420)	21.5 (541)	22.5 (563)	140 (60)	77 (35)
D144IN	144	85	0.57	115/1/60	1/2"	16.5 (420)	21.5 (541)	22.5 (563)	140 (60)	82 (37)
D180IN	180	106	0.71	115/1/60	1"	16.5 (420)	21.5 (541)	22.5 (563)	140 (60)	104 (47)
D300IN	300	176	1.25	230/1/60	1-1/2"	20.0 (503)	25.5 (644)	38.5 (980)	140 (60)	192 (87)
D360IN	360	212	1.25	230/1/60	1-1/2"	20.0 (503)	25.5 (644)	38.5 (980)	140 (60)	192 (87)
High Temperature										
D25IT	25	15	0.21	115/1/60	1/2"	15.5 (386)	20.0 (500)	26.0 (661)	200 (94)	84 (38)
D42IT	42	25	0.37	115/1/60	1/2"	15.5 (386)	20.0 (500)	26.0 (661)	200 (94)	86 (39)
D60IT	60	35	0.37	115/1/60	1/2"	15.5 (386)	20.0 (500)	26.0 (661)	200 (94)	86 (39)
D102IT	102	60	0.48	115/1/60	3/4"	16.5 (420)	22.5 (567)	30.5 (771)	200 (94)	126 (57)
D140IT	140	82	0.57	115/1/60	3/4"	16.5 (420)	22.5 (567)	30.5 (771)	200 (94)	137 (62)
D170IT	170	100	0.71	115/1/60	1"	16.5 (420)	22.5 (567)	30.5 (771)	200 (94)	148 (67)

Notes:

- 1) Dryer is rated for a ISO Class 6 Dew Point in accordance with ISO8573-1.
- 2) Performance data presented in accordance with CAGI Standard ADF 100 using 100°F inlet temperature, 100°F ambient temperature and 100 psig conditions. (150°F inlet and 95°F ambient for High Temperature dryers).



Ingersoll Rand Industrial Technologies provides products, services and solutions that enhance our customers' energy efficiency, productivity and operations. Our diverse and innovative products range from complete compressed air systems, tools and pumps to material and fluid handling systems and environmentally friendly microturbines. We also enhance productivity through solutions created by Club Car®, the global leader in golf and utility vehicles for businesses and individuals.

www.ingersollrand.com www.clubcar.com

Industrial Technologies

P.O. Box 1840
800-D Beaty Street
Davidson, NC 28036
(704) 655-5000
(704) 655-4039 Fax



Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service.

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request.

Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.