

# 80-Gallon

STATIONARY - ELECTRIC - TWO STAGE

The ultimate in tank capacity! Perfect for shops and service bays where compressed air is considered a fourth utility.




AM2-SE05-80M


**Compressor Pump:** Splash lubrication cast iron crankcase · Cast iron head for heat dissipation · Cast iron cylinder · Large canister intake filter · Intercooler · Oil sight glass

**Frame:** Powder coated ASME coded 80-gallon receiver tank · 3/16-inch base plate to reduce vibration · 14-gauge powder coated two-piece belt guard

**Components:** Large fly wheel for extra cooling and longer life · Manual tank drain valves and pump oil drain for maintenance · Steel braided supply line hose



Quality splash lubricated cast iron two stage compressor



Industrial 1740 RPM UL-listed electric motor with NEMA-4 starter box with magnetic starter



Industrial grade pressure switch and tank gauge

**1 YEAR LIMITED ELECTRIC MOTOR WARRANTY** **2 YEAR LIMITED WARRANTY** **2 YEAR LIMITED PUMP EXCHANGE PROGRAM**



CSA Certified:  
AM2-SE05-80M  
AM2-S305-80M

**Best Pump Warranty in the Industry**  
See p. 44 for details

Model No.	CFM @ 175 PSI	Horsepower	Pump	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM2-SE05-80M	16.9	5.0 HP Electric	Cast iron	34in.x26in.x72.5in.	585 lbs.	466 lbs.
AM2-S305-80M <sup>^</sup>	16.9	5.0 HP Electric	Cast iron	34in.x26in.x72.5in.	526 lbs.	407 lbs.
AM2-VE75-80M	24.0	7.5 HP Electric	Cast iron	24in.x35in.x66in.	610 lbs.	491 lbs.

<sup>^</sup>Three-phase unit.

**Options** (Consult price list or [www.mitm.com](http://www.mitm.com) for more information on option descriptions and qualifying models)

- AX-0044 230V, Single-phase, 31.0A, 7.5 HP - Configures unit for 230V single-phase power
- AX-0045 200V, Three-phase, 23.0A, 7.5 HP - Configures unit for 200V three-phase power
- AX-0046 230V, Three-phase, 20.0A, 7.5 HP - Configures unit for 230V three-phase power
- AX-0047 460V, Three-phase, 10.0A, 7.5 HP - Configures unit for 460V three-phase power
- AX-0058 230V, Single-phase, 23.0A, 5.0 HP - Configures unit for 230V single-phase power
- AX-0059 200V, Three-phase, 16.1A, 5.0 HP - Configures unit for 200V three-phase power
- AX-0060 230V, Three-phase, 13.8A, 5.0 HP - Configures unit for 230V three-phase power
- AX-0061 460V, Three-phase, 6.9A, 5.0 HP - Configures unit for 460V three-phase power

\*All options add starter to model.