


0° to 40°

WEAR TEST

NEW NOZZLE

Céramic

Stainless steel



NOZZLE AFTER 50 h TEST

Céramic

Stainless steel



Ceramic is an exceptional material :

The orifice of the ALBUZ TEC UAS range of nozzles is a white ceramic. This ceramic material was specifically developed for high pressures and, is almost as wear resistant as diamond. The properties of the ceramic material are the keys to successful industrial nozzles applications :

- High mechanical resistance
- Corrosion resistance
- High hardness
- Resistance to high temperatures
- Resistance to high pressures
- Exceptional wear resistance
- Ultra smooth surfaces.

General characteristics :

- ALBUZ TEC ceramic inserts (excellent precision, high wear resistance)
- Flat fan jet angles from 0° to 40° at 40 psi
- Maximum pressure : 300 bar (4330 PSI)
- Maximum temperature : 125°C (276° F)
- Body model : Stainless steel AISI 304 L
- The U form insert allows better flow characteristics at high pressures
- Smooth surfaces allow better flow characteristics.

Wear resistance :

- Nozzle wear generally depends on three parameters :
 - The pressure (the higher pressure, the higher wear)
 - The abrasiveness of the fluid (the more solids the higher the wear)
 - The corrosive nature of the fluid.
- After hours of use with abrasive, corrosive and or high pressure fluids, traditional nozzles will deteriorate the internal hole, enlarging the diameter, increasing the flow rate changing the spray configuration and modifying the droplet size and distribution. Thanks to the exceptional material characteristics of the ALBUZ TEC ceramic material, the UAS nozzle range proves it's cost effectiveness through longer life and better performances.

