

## WAGAN Corp. Limited Warranty Registration Form

All WAGAN Corporation products are warranted to the original purchaser of this product.  
**Warranty Duration:** This product is warranted to the original purchaser for a period of one (1) Year from the original purchase date, to be free of defects in material and workmanship. WAGAN Corporation disclaims any liability for consequential damages. In no event will WAGAN Corporation be responsible for any amount of damages beyond the amount paid for the product at retail. In the even of a defective item, please ship the item, prepaid, with a complete explanation of the problem, your name, address and daytime phone number. WAGAN Corporation will, at its option, replaces or repair the defective part. This warranty is void if the product has been damaged by accident, in shipment, unreasonable use, misuse, neglect, improper service, commercial use, repairs by unauthorized personnel or other causes not arising out of defects in materials or workmanship. This warranty is effective only if the product is purchased and operated in the USA and does not extend to any units which have been used in violation of written instructions furnished.  
**Warranty Disclaimers:** This warranty is in-lieu of all warranties expressed or implied and no representative or person is authorized to assume any other liability in connection with the sale of our products. There shall be no claims for defects or failure of performance or product failure under any theory of tort, contract or commercial law including, but not limited to negligence, gross negligence, strict liability, breach of warranty and breach of contract.  
**Warranty Performance:** During the above one (1) Year warranty period, a product with a defect will be replaced with a comparable model when the product is returned to WAGAN Corporation with an original store receipt. The replacement product will be in warranty for the balance of the one (1) Year warranty period.

- Please activate my limited warranty for WAGAN Corp. Heavy Duty Air Compressor
- Enclosed copy of original sales receipt.

Name			
Mail Address			
City			
State, Zip Code			
Item Purchased	Heavy Duty Air Compressor		
Stores Name			
Date of Purchase			
Signature		Date	

All WAGAN Corporation Products must be registered within (30) days of purchased to activate this warranty. Mail the complete registration form, along with a copy of the original receipt to:

Attn: Customer Service  
 WAGAN Corporation  
 3589 Yale Way  
 Fremont, CA 94538

© 2004 WAGAN Corp.



Item no. 2050

# Heavy Duty Air Compressor™



***User's Manual***

# Heavy Duty Air Compressor by Wagan Tech

USER'S MANUAL — Please read before using this equipment.

Thank you for purchasing the Heavy Duty Air Compressor by Wagan Tech. With normal care and proper treatment it will provide years of reliable service. Please read all operating instructions carefully before use.

## TO INFLATE TRUCK, UTILITY VEHICLE, CAR, AND MOTORCYCLE TIRES:

1. To achieve optimal performance, when operating your air compressor, your vehicle's engine should be running.
2. Plug the compressor's power cord into the 12-volt cigarette lighter socket of your vehicle. Screw the air hose's brass valve tip directly onto the tire's air valve.
3. Turn the compressor ON - begin to inflate tire.
4. When the pressure gauge indicates the desired pressure. Switch the unit OFF and remove the air hose from the valve (normal tire pressure is 28 - 35 PSI).

## PRECAUTIONS:

1. Built-in to this unit is an automatic reset thermal overload protector which will shut off motor if it becomes overheated. The protector will automatically reset when the motor cools down
2. Allow sufficient cooling time before storing
3. All parts are lifetime lubricated, and no oiling is required
4. To avoid low voltage of auto battery, please have the engine running when using the air compressor

5. Be sure the unit's power switch is in the OFF position when not in use

## FOR ALL OTHER INFLATABLE OBJECTS INCLUDING BICYCLE TIRES, INFLATABLE BOATS, AIR BEDS, AND ATHLETES BALLS:

1. Start your vehicle's engine, then plug the compressor's power cord into the 12 volt cigarette lighter socket of your vehicle.
2. A selection of nozzles is provided to fit most inflatable objects. Simply screw the appropriate nozzle into the brass tip of the air hose.
3. Attach the appropriate nozzle to the inflatable object and turn on the power switch. When the object is inflated to desired firmness or pressure, turn the compressor off.

## SPECIFICATIONS:

Voltage: DC 12 V – 13.5 V  
Current Consumption: Max. 14 Amp.  
Flow Rate: 35 L / Min.  
Max. Pressure: 10 kg /cm (143 PSI)  
Working Pressure: Max. 7 kg /cm (100 PSI)  
Weight: 5.40 lb  
Ambient Temperature: -20°C ~ 80°C