

GP SERIES

COMMERCIAL / RESIDENTIAL PORTABLE GENERATORS

FEATURES:

- High performance brushless alternator
- Steel fuel tank with incorporated fuel gauge
- Mobility kit with locking fold-down handles and never-flat wheels
- 1-1/4" diameter hardened steel tube cradle
- Hour meter with maintenance resets
- Circuit breaker protected outlets
- Low-tone muffler

GP5000

Model 05622

Running Watts: 5000

Starting Watts: 6250



Ratings	
AC Rated Output	5kW / 5000 Watts
AC Maximum Output	6.25 kW / 6250 Watts
AC Voltage	120V/240V
AC Frequency	60 Hz
120 VAC Amperage	Rated 41.6/Max 52.1
240 VAC Amperage	Rated 20.8/Max 26.0
Engine	
Engine Type and Displacement	OHV Single Cylinder 389cc
Oil Capacity	1.1 Qt. (1.16 liter)
Low Oil Shutdown	Standard

Fuel	
Fuel Capacity	6.6 Gallons (24.98 liters)
Run Time @ ½ Load	10 Hours
Assembled Dimensions and Weight	
Dimensions L x W x H (inches)	33.5 x 26.5 x 27.5
Dimensions L x W x H (mm)	850.9 x 673.1 x 698.5
Unit Weight	180 lbs. (81.6 kg.)
Warranty	
Residential	2 Year Limited
Commercial	1 Year Limited

Outlets

4 x 5-20R



1 x L14-30R



Maximum wattage and current are subject to, and limited by, such factors as fuel Btu content, ambient temperatures, altitude, engine condition, etc. Maximum power decreases about 3.5% for each 1,000 feet above sea level; and will also decrease about 1% for each 6° C (10° F) above 16° C (60° F) ambient temperature.