



JP Series

Industrial Cold Water Pressure Washers

Electric — Portable — Direct Drive



JP-2503-1ME3

This is the perfect unit for food and beverage processing facilities where fumes and smoke are prohibited. Tackle indoor jobs along with those tough outdoor cleaning tasks.

PUMP

- Adjustable pressure unloader
- Forged brass manifold (Nickel plated brass on 2ME1 models)
- Thermal and safety relief valves
- Built-in low pressure detergent injector

MOTOR

- Totally enclosed fan-cooled electric motor
- 35-foot power cord with GFCI (JP-1002 to JP-2503 single-phase models) (10-foot power cord on JP-3004 models)

FRAME

- Powder coated steel frame
- 13-inch flat-free tires (10-inch tires on JP-1002, JP-1502 and JP-2003 models)

UNIT INCLUDES

- Variable high/low pressure nozzle (JP-1002, JP-1502 and JP-2003 models)
- Quick connect nozzles – 15°, 25° and detergent nozzle (JP-2503-2ME1 and JP-3004-2ME1)
- Quick connect nozzles - 0°, 15°, 25° and detergent nozzle (JP-2503-1ME3 and JP-3004-1ME3)
- 50-foot x 3/4-inch non-marking hose (25-foot on JP-1002, JP-1502 and JP-2003 models)
- 36-inch lance with insulated trigger gun

LIMITED WARRANTIES

- 1 year electric motor
- 7 year AR and General pumps

CERTIFICATION

- CSA Certified – US and Canada (JP-1002-2ME1 and JP-1502-2ME1)
- CSA Certified – US only (JP-2003 models)
- Intertek Certified to UL-1776 – US only (JP-2503 and JP-3004 models)



JP Series

Cold Water – Electric – Portable – Direct Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-1002-3ME1	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	AR	NEMA 5-15P	37x21x24.5in.	120 lb.	90 lb.
JP-1002-4ME1*	1000	2.0	1.5 HP, 120V, 1Ø, 13.2A	General	NEMA 5-15P	37x21x24.5in.	120 lb.	90 lb.
JP-1502-3ME1	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	NEMA 5-20P	37x21x24.5in.	120 lb.	90 lb.
JP-1502-4ME1*	1500	2.0	2.0 HP, 120V, 1Ø, 17.5A	General	NEMA 5-20P	37x21x24.5in.	120 lb.	90 lb.
JP-2003-3ME1	2000	2.6	4.0 HP, 230V, 1Ø, 16.0A	AR	NEMA 6-20P	40x22.5x24.5in.	162 lb.	112 lb.
JP-2503-2ME1	2500	3.2	6.0 HP, 230V, 3Ø, 17.3A or 6.0 HP, 460V, 3Ø, 8.65A	AR	NEMA 6-30P	40x22.5x24.5in.	275 lb.	225 lb.
JP-2503-1ME3	2500	3.2	6.0 HP, 230V, 3Ø, 17.3A or 6.0 HP, 460V, 3Ø, 8.65A	AR	NEMA L15-20P	40x22.5x24.5in.	275 lb.	225 lb.
JP-3004-2ME1	3000	3.9	8.0 HP, 230V, 1Ø, 30.5A	AR	NEMA 6-50P	40x22.5x24.5in.	275 lb.	225 lb.
JP-3004-1ME3	3000	3.9	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	AR	NEMA L15-30P	40x22.5x24.5in.	275 lb.	225 lb.

*Pump accepts incoming water up to 175°F.

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODEL
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	All models
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	All models
CX-0030	50-foot x ¾-inch non-marking hose – For when you need extra hose for added mobility	1000 to 2000-PSI models
CX-0066	460V on 6.0-HP 3Ø model – When 460V of power is available	JP-2503-1ME3
CX-0067	460V on 8.0-HP 3Ø model – When 460V of power is available	JP-3004-1ME3



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA L15-20P,
20-amp plug



NEMA 6-20P,
20-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-30P,
30-amp plug



NEMA 6-50P,
50-amp plug

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.