

TECHNICAL DATA - FIXED SPEED COMPRESSORS	
Product Information	
Model	KRSL-100-45
Cooling	Air cooled
Power Supply - Voltage	460V
Power Supply - Frequency	60Hz
Power Supply - Phases	3-Phase
Type of drive	Direct
Maximum ambient temperature - °F	115
Minimum ambient temperature - °F	32
Compressor Performance*	
Rated Working Pressure - psig	36
Minimum working pressure - psig	30
Maximum working pressure - psig	45
Capacity at rated Working Pressure - acfm	1010
Total input Power at rated Working Pressure – kW	95.2
Specific Power at rated Working Pressure-kW/100 cfm	9.4
Electrical Data (Typical)	
Motor rated HP	100
Motor Nominal Efficiency %	95.4%
Motor frame	TEFC
Service Factor	1.3
Starter Type	Y-∆
Motor Protection	IP54
Electrical enclosure rating	NEMA 1
Full Load Package Amps	
Full load package amps - 460 V/60 Hz	156
Full load package amps - 230 V/60 Hz	312



RESSORS	
Dimensions & Weights w/Enclosure Air-cooled Series	
113	
69	
81	
7715	
NPS5	
-	
17	
74	
9888	
5	
Centrifugal	
99.9% Eff.	
23µm	
3ppm	
Single stage	
WEG	
IEC	
Modulation	
Low sound	

Effective - June 2023