



Piston Technical Data Sheet

QT-5

HP	5	cfm@100psi	17.7
Low Pressure_Bor	4"	cfm@175 psi	17.2
High Pressure_Bor	2.5"	Pump Speed	942
Stroke	3"	80 Gal V	80 Gal H
Max Working Press	175	Dims (LxWxH)	37x24x74 70X23X47
Inlet Size	1" NPT	Weight	680 660
Air Outlet Size	3/4" BALL VALVE		
Min/Max RPM	400-1060 RPM		
Pump Life	50,000 hrs	Tank Pressure	200 psi
Duty Cycle	100%	Tank Fill Time	7.4 min
Lubrication	Quin-Cip		
Sump Capacity	1 qt. & 20 oz. (1.53 lit.)	Standard Warranty	Factory - 12 months parts / 12
Noise _dB(A)	78 ± 3	Extended Warranty	3-Year Pump/ 2-Year Package Warranty
Min operating_Temp	0 deg F	EWK part number	EWK-3
Max operating Temp	104 deg F	EWK Contents	1 Air Filter, 6 qts Quin-Ciip D

*Duplex unit owners must purchase two (2) EWK kits
 *Engine-driven unit extended warranty is on air compressor only, "less engine". See engine manufacturer for warranty coverage.

Voltage:	120/1	230/1	200/3	230/3	460/3	575/3
Amp Draw:	-	28	17.5	15.2	7.6	6.1

*Applicable data doubled for Duplex models