



SPECIFICATION SHEET

Product	Electric powered lubricated screw air compressor	Type :EG37 208-230/460V /	Date(Org):11/05/2017
Doc. Category :	Marketing	Revision : R06	Date(Rev):25/04/2019
S.No	Description	Units	Data
A	Model	-	EG 37-100 EG 37-125 EG 37-150 EG 37-175
B	TPL Number	-	S014260 S014261 S014262 S014263
1	Free air delivery - FAD	cfm	248 212 203 172
		m3/min	7.02 6.00 5.75 4.87
2	Working pressure	psi.g	100.0 125.0 150.0 175.0
3	Unloading pressure	psi.g	107.0 132.0 157.0 182.0
4	Package Input power @ 100% flow	hp (kW)	57.81(43.13) 55.84(41.66) 60.95(45.47) 58.11(43.35)
5	Package input power @ zero flow	hp (kW)	16.09(12.00) 15.55(11.60) 16.09(12.00) 15.42(11.50)
6	Specific power consumption @ full load	kW/100cfm	17.39 19.65 22.40 25.20
7	Capacity control system	-	Load / Unload
8	Nominal power supply conditions		208-230 / 460V (+/-10%), 60Hz(+/-5%), 3 Phase
9	Main motor rating	hp (kW)	50.0(37.0)Normal Rating with SF1.15 Continuous duty
10	Type of motors (main drive & cooling fan drive)	-	Squirrel Cage Induction - TEFC & Cooling Fan Integrated Motor
11	Insulation and protection of main motor	-	Class F / IP55
12	Frame size / Mounting type	-	326T / B35T
13	Efficiency class of main motor	-	94.5%/NEMA-PREMIUM
14	Type of starter for main motor	-	Automatic star delta
15	Fan motor rating per fan x No. of fans	hp (kW)	2.07 (1.55) - 208V-230V/460V
16	Rated speed of fan motor	rpm	1320 (208V-230V) / 1420 (460V)
17	Max allowable package current with Fan at nominal power supply	Amps	154.1 (208V) / 140.3 (230V) / 70.8 (460V)
18	Type of coupling		Flexible jaw coupling with snap wrap element
19	Flow rate of cooling air @ static pressure (Pa)	cfm	4708 @ 140 Pa
20	Oil recommended	-	ELGI AIRLUBE UT SYNTHETIC
21	Capacity of seperator tank (full volume)	gal	13.3
22	Total oil fill capacity	gal	5.3
23	Oil carry over	ppm	<1.0
24	Reference conditions - ambient & altitude	°F/ ft	95 & 3280
25	Discharge oil temperature	°F	Minimum: Above PDP at given pr. & 90% RH Maximum: Ambient +111.6
26	Maximum allowable air temperature at outlet	°F	Ambient +18
27	Noise level of the compressor	dB (A)	69
28	Air outlet port size	inch	1 1/2" NPT Thread
29	Overall dimensions of the unit, L x B x H	inch	67.12 X 43.7 X 61.81
30	Overall dimensions with packing, L x B x H	inch	75.2 X 51.57 X 69.1
31	Package nett. weight (dry condition)	lbs	2447
32	Package Gross Weight with packing	lbs	2535
33	Reference standard for FAD and SPC	-	ISO 1217- Annexure 'C '
34	Reference standard for noise level	-	ISO 2151, Second Edition
35	Reference standard for air purity	-	ISO 8573-1

Note:-

Prepared By	VIGNESH P	Approved By	JAYARAJ B
All data and information in this sheet are confidential and property of ELGI EQUIPMENTS LIMITED			
This is system generated document and hence signature is not required			