

PS-421

Compact class chain saw

Now, professional and occasional users can enjoy all the benefits of DOLMAR's large saws, in a smaller, more comfortable package! The compact class is designed to the same rugged performance characteristics of our larger saws



Large, easy accessible tank caps



The externally mounted sprocket makes fitting the chain simple and uncomplicated



Touch&Stop one lever operating



Die-cast magnesium engine block for strong torque production

Technical specifications

Engine manufacturer	DOLMAR	Oil tank capacity	0.28 l (9.5 oz)
Displacement	42.4 cc (2.5 cu. in)	Standard guide bar	14"
Power rating	2.2 kW (2.9 HP)	Optional guide bar	16"
Max engine speed	13,500 rpm	Chain pitch	3/8 "
Net weight	4.9 kg (10.8 lbs)	Chain gauge	.050 "
Fuel tank capacity	0.48 l (16.2 oz)		

- Easy Start: Spring assisted starter combined with optimized engine management significantly reduces resistance
- SafetyMatic chain brake
- Centrifugal clutch with 3 weights
- Outside sprocket
- Adjustable oil pump, disabled at engine idling
- Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.
- Magnesium diecasting housing
- Catalytic converter to clean the exhaust gases
- Toolless airfilter maintenance
- Lateral chain tensioning
- Summer / winter operation
- Big tank cap, easy reachable. S-form with acme thread for easy operation

DOLMAR Power Products · PO Box 5007 · Alpharetta, GA 30023-5007

www.dolmarpowerproducts.com

www.dolmar.com

