

PS-5105

Powerful, agile and reliable


The formula for the professional mid-range model, with high torque for felling and stripping of mid-sized trees, but also ideal for de-branching operations because of its ergonomic design, high RPM and racy acceleration.



Thanks to smooth surfaces, the models are easy to handle and clean



The advantageous chain space is easy to clean and lets the chips fly where they may



Lateral chain tensioning



Optimum chip exhaust for avoiding jams

Technical specifications

Displacement	50 cc (3.1 cu. in)	Fuel tank capacity	0.47 l (15.9 oz)
Engine manufacturer	DOLMAR	Oil tank capacity	0.27 l (9.1 oz)
Power rating	2.8 kW (3.9 HP)	Standard guide bar	16", 18"
Max engine speed	13,800 rpm	Optional guide bars	20"
Net weight	5.4 kg (11.9 lbs)	Handle Heating	no

- MPI technology (Memory-Power-Ignition) for easy restart
- Catalytic converter to clean the exhaust gases
- Powerful engine for felling and chopping medium-thick wood
- Good cooling for a high reliability
- High rpm and super-fast acceleration
- Ergonomic design, easy handling
- Tool-less filter maintenance
- Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.
- Lateral chain tensioning
- Optimum chip flow through
- Adjustable oil pump, disabled at engine idling

DOLMAR Power Products • PO Box 5007 • Alpharetta, GA 30023-5007

www.dolmarpowerproducts.com

www.dolmar.com

