



Thermoplastic Sump Pump

High-Output Performance



Energy Efficient Design
Diseño Eficiente de la Energía
Conception rationnelle de l'énergie



Thermoplastic construction

Resists corrosion

Zinc motor housing

Dissipates heat quickly and extends motor life

Stainless steel fasteners and hardware

Superior quality

Smooth Flow Hydraulics™

Deliver high performance for demanding applications

Tethered float switch

Operates in 14" basins or larger

1/4 HP 3200 GPH
FPZS25T

1/3 HP 3600 GPH
FPZS33T

1/2 HP 4200 GPH
FPZS50T

PERFORMANCE (GPH)							FLOAT SWITCH		SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	MAX. LIFT	ON	OFF	
FPZS25T	3,200	2,700	2,160	1,500	-	20'	14"	5"	3/16"
FPZS33T	3,600	3,060	2,400	1,680	660	22'	14"	5"	3/16"
FPZS50T	4,200	3,660	3,000	2,160	960	22'	14"	5"	3/16"

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FPZS25T	1 YEAR	022315368453	8" x 6" x 12.75"	105	7.7 LBS.
FPZS33T	1 YEAR	022315368460	8" x 6" x 12.75"	105	7.7 LBS.
FPZS50T	1 YEAR	022315368484	8" x 6" x 12.75"	105	10 LBS.

Includes: 1 1/2" NPT discharge, 8' grounded power cord, piggyback-style switch for automatic or manual operation, detailed owner's manual

Check Valve replacement is recommended

293 Wright Street, Delavan, WI 53115

For Questions or Installation Instructions:

www.flotecwater.com 1-800-365-6832

