

Check out other Tsurumi Pumps designed fo low-level pumping and remove standing water from...



Road Construction



Parking Lots



Roof Tops



Basements



Sport Facilities



LSC1.4S - Floor Level Drainage Pump

Internal check valve allows LSC pump to hold prime for:

- start-up at any water level
- pump down to any surface
- prevention of back-flow when turned off

LSR2.4S - Ground Level Drainage Pump

Top discharge, angle coupling design allows for:

- continuous operation at low water levels without overheating motor
- easy change to vertical or horizontal discharge

www.tsurumipump.com

Tsurumi (America), Inc. • 1625 Fullerton Court, Glendale Heights, IL 60139 • Tel: 888-878-7864 (toll-free)

HS2.4S Residue Kit Installation Guide

The RESIDUE KIT provides a low water level pump down by simply replacing the standard Strainer Stand of your Tsurumi HS2.4S Sand/Trash Pump with this Residue Kit.



Residue Kit Installed on
Tsurumi HS2.4S Sand/Trash Pump



Step 1:



Make sure your Residue Kit has all components on hand:

- Residue plate
- Hex bolt M8 x 65 (Qty 3)
- Flat washer M8 (Qty 3)
- Nylon Spacer M8 (Qty 3)

Step 2:



Remove the strainer stand from pump by removing the (3) M8 nuts using a 13mm wrench or socket.

Step 4:



Replace the pump casing / discharge assembly to the pump assembly and place either set of (3) flat washers (for lowest pump down level), or (3) nylon spacers (to retain solids handling capability).

<CAUTION> Use the nylon spacer option when the pump is used on a finished surface or flexible material such as a swimming pool or pond liner.

Step 5:



Place the residue plate, assuring that the bolt through-holes are aligned with the washers or spacers. Install the (3) M8 x 65mm hex bolts from the Residue Kit as illustrated.

Step 3:



Lift the pump assembly from the pump casing / discharge assembly and invert the pump upside down on a sturdy level surface. Block the pump in place as illustrated to assure it is stable during installation of the residue plate.

If a suitable size block is not available, the strainer stand may be used to support the pump.

Step 6:



To complete the Residue Kit installation, reinstall the (3) nuts removed in Step 2, and carefully return the pump to its upright position.

<CAUTION> When small stones are present, clear a large area free of stones and place the pump on a hard level surface (such as a board) to prevent stones from passing through the pump.