



Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

PUMP COMPANY

Zoeller Family of Water Solutions™

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
 SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
 (502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:
www.zoeller.com

COMPARE THESE FEATURES:

- Use fully or partially submerged
- Durable polypropylene housing
- 3-prong power cord, 9 ft. or 20 ft.
- 115 Volt/Single Phase/60 Hz
- High-quality sealed motor
- Thermal-overload protected motor
- Model 42 is adaptable for use with standard garden hose (fitting included), 1" NPT pipe, or 1/4" slip fit (use discharge hose kit P/N 1010-0117)
- Model 44 is adaptable for use with standard garden hose (fitting included) 1-1/4" female NPT or 3/4" female NPT adapter
- Model LM44 with automatic operation. Utility applications only*
- Model 46 has 2" NPT discharge with 2" hose adapter
- Screened bottom may be removed to allow easy cleaning.
- Use indoors or outdoors
- Typical applications: dewatering and filling
- Oil free (Models 42 and 44 only)
- Models 42 and 44 remove water from any flat surface down to 1/8", model 46 will pump down to 1"
- Lightweight and portable
- Compact design: models 42 and 44 will fit in a 7" opening; model 46 will fit in an 8" opening
- One-year limited warranty
- Temperature rating 104°F (40°C)
- Nonautomatic - 42, 44 and 46 models

| Model | HP | Amps | Max Width | Max Height | Weight |
|-------|-----|------|-----------|------------|----------|
| 42 | 1/6 | 1.5 | 6 | 9-1/2 | 7.3 lbs. |
| 44 | 1/4 | 2.5 | 6 | 11-3/4 | 7.7 lbs. |
| LM44 | 1/4 | 2.5 | 6 | 11-3/4 | 8.7 lbs. |
| 46 | 1/2 | 6.0 | 8 | 14-1/2 | 16 lbs. |

TOTAL DYNAMIC HEAD FLOW PER HOUR

| MODEL | | 42 | | 44 | | 46 | |
|---------------|--------|----------------|--------|----------------|--------|-----------------|--------|
| Feet | Meters | Gal. | Liters | Gal. | Liters | Gal. | Liters |
| 5 | 1.5 | 900 | 3407 | 1800 | 6814 | 3300 | 12492 |
| 10 | 3.0 | 660 | 2498 | 1320 | 4997 | 2820 | 10675 |
| 15 | 4.6 | 360 | 1363 | 720 | 2725 | 2160 | 8176 |
| 20 | 6.1 | --- | --- | --- | --- | 1500 | 5678 |
| 30 | 9.1 | --- | --- | --- | --- | 300 | 1136 |
| Shut-off Head | | 19 ft. (5.8 m) | | 20 ft. (6.1 m) | | 34 ft. (10.4 m) | |

* Model LM44 not to be used as a sump pump.

MODEL 42 - 44 - 46

FLOOR SUCKER SERIES

UTILITY PUMPS



**1/6 HP
Model 42**



Certified to CSA
Standard C22.2 No. 108



**1/4 HP
Model 44**



**1/4 HP
Model LM44
Automatic**



SSPMA
Certified
100 YEARS



**1/2 HP
Model 46**

USE FLOOR SUCKER SUBMERGED OR ON ANY FLAT SURFACE TO PUMP CLEAR WATER.