

## 30 CFM – 144 CFM Premium Industrial Refrigerated Air Dryers



• Purifies compressed air by chilling to condense moisture

5 YEAR

- High Refrigerant Safety
- Condensate is drained carrying oil and dirt particles away from the air
- Outlet air baffle heater prevents condensation on outlet air piping
- Heavy duty steel cabinet
- Trouble free operation refrigerated air inlet inner cooler for high temp cooling
- Side mounted condenser & Fan Motor
- Environmentally friendly 134A refrigerant
- Pre-Plumbed
- 5 Micron Pre-Filter
- Quick, Easy to Remove Cabinet Door for Easy Servicing - No Screws!

			50000	
	EDRCF1150030	EDRCF1150058	EDRCF1150115	EDRCF1150144
CFM	30	58	115	144
Pipe Size	1/2"	3/4"	1 1/2"	1 1/2"
Voltage 60hz	115	115	115	115
Amperage	4	7.2	11	14
Filteration	Built in Coalscing	Built in Coalscing	Built in Coalscing	Built in Coalscing
Dew Point (F)	37-50	37-50	37-50	37-50
Max Working PSI	230	230	230	230
Max Inlet Temp (F)	140	140	140	150
Refrigerant Type	134A	134A	134A	134A
Max Ambient Temp	122	122	122	120
Drain Type	Automatic	Automatic	Automatic	Automatic
Dims: LXWXH	16" x 18" 24"	24" x 19" x 30"	26" x 23" x 36	26" x 23" x 36
Weight ( LBS)	110	120	180	180

1000 Cass Drive Englewood, OH 45315 Toll Free: 866-294-4153 Fax: 937-540-1157 5 Yr- Limited warranty on heat exchanger 2 YR- Limited warranty on all other parts



www.emaxcompressor.com