

# NCC199CDV

## Next Gen True Commercial Tankless

GQ-C3260WZ-FF US

The rolling update to the NCC199CDV provides industry leading performance for any commercial water heating application. An impressive 10-year heat exchanger warranty comes included, providing businesses with years of hot water without the worry. In addition, the NCC199CDV now eliminates the need to purchase additional accessories by featuring a built-in exhaust non-return valve.

## UPDATED FEATURES

### ⇒ **NEW Built-In Exhaust Non-Return Valve**

The new built-in exhaust non-return valve allows for common venting of up to 6 heaters without the need for additional accessories.



### ⇒ **10 Year Commercial Warranty**

The NCC199CDV features an industry-leading 10 year heat exchanger warranty.

### ⇒ **Upgraded Stainless Steel Heat Exchangers**

Developed with high grade stainless steel, our NCC199CDV comes with 2 heat exchangers that are built to last.

### ⇒ **Higher, Industry-Leading Efficiency**

Combined with a unique negative pressure Venturi gas valve, the NCC199CDV offers 0.97 UEF, minimizing carbon emissions.



## SPECIFICATIONS

		NCC199CDV
<b>Weight</b>		70 lbs.
<b>Capacity Range</b>		0.5 - 11.1 GPM (30° F Rise)
<b>Min / Max BTU</b>		18K - 199,900 BTUh
<b>UEF</b>		0.97
<b>Thermal Efficiency</b>		98%
<b>Connection Sizes</b>	Water Inlet	NPT 3/4"
	Hot Water Outlet	NPT 3/4"
	Gas Inlet	NPT 3/4"
	Condensate Drain	NPT 1/2"
<b>Water Holding Capacity</b>		0.82 Gallon (3.1 L)
<b>Temperature Settings</b>	° F Mode	100-150°F (In 5°F Intervals) 160°F, 170°F, 185°F (14 options)
	° C Mode	37-48°C (In 1°C Intervals), 50-85°C (In 5°C Intervals) (20 Options)
<b>Operating Pressure</b>		15 - 150 psi (Recommended 50 to 80 psi for maximum performance)
<b>Included Accessories</b>		Remote controller, remote controller cord, anchoring screws, wall mounting bracket

### Optional Parts List

Part Name	Part #
Wifi Adapter	NWCC-ADAPTER
Outdoor Vent Cap	VC-6
System Controller	SC-401-6M
	SCU-401-12M (12 unit)
	SCU-401-24M (24 unit)