

NOTHING CUTS LIKE AN IKON.

IKON X SERIES

Show the neighborhood that you mean business with this commercial grade machine. Packed with premium features, this zero-turn is designed to deliver professional results.



- Commercial Style Deck- 4 1/2" deep fabricated deck provides airflow in challenging mowing conditions delivering excellent cut quality
- Tubular Steel Frame- Fully-welded tubular steel frame provides superior strength and stability over competitive c-channel frame designs
- **Dial-Operated Cutting Height** 13 cutting positions at your fingertips, allows for adjustments from 1 1/2" to 4 1/2" in 1/4" increments with the turn of a dial
- Hydro-Gear® EZT Transaxles- provide a smooth driving experience
- Comfort- The plush, high-back seat comes standard with armrest and a contoured rubber foot mat isolate vibration producing superior ride comfort
- **Powerful Engine Options** Kohler® 7000 series™ and Kawasaki® V-Twin engine options provide the driving force behind this zero-turn

SPECIFICATIONS

| | IKON 42 | IKON 52 | IKON 52 |
|---|--|--|---|
| Model Number | 915220 | 915222 | 915223 |
| ENGINE | Kohler® 7000 Series | Kohler® 7000 Series | Kawasaki® FR Series |
| HORSEPOWER | 22 | 24 | 23 |
| DISPLACEMENT (cc) | 725 | 725 | 726 |
| DRIVE SYSTEM | Hydro-Gear $^{\circ}$ EZT transaxles w/ I" axle shafts & 7" Fans | Hydro-Gear® EZT transaxles w/ I" axle shafts & 7" Fans | Hydro-Gear® EZT transaxles w/ I" axle shafts & 7" Fal |
| UEL CAPACITY - Gallons (LITERS) | 2.8 (10.5) | 2.8 (10.5) | 2.8 (10.5) |
| GROUND SPEED (APPROX. Mph) For/Rev | 7 mph/3 mph | 7 mph/3 mph | 7 mph/3 mph |
| STARTER | Electric | Electric | Electric |
| DECK | | | |
| DECK MATERIAL | lOga Steel | lOga Steel | lOga Steel |
| DECK CONSTRUCTION | Fabricated | Fabricated | Fabricated |
| NUMBER OF SPINDLES | 3 | 3 | 3 |
| BLADE TIP SPEED (FPM) | 17.000 | 17.000 | 17,000 |
| SPINDLE MATERIAL | Aluminum | Aluminum | Aluminum |
| SPINDLE SHAFT | l"Dia. Steel | l"Dia. Steel | l"Dia. Steel |
| SPINDLE BEARINGS | l" Sealed | l" Sealed | l" Sealed |
| DECK DRIVE | Belt | Belt | Belt |
| DECK ENGAGEMENT | Electric Warner® | Electric Warner® | Electric Warner® |
| DECK LIFT SYSTEM | Foot Operated | Foot Operated | Foot Operated |
| CUTTING WIDTH | 42° | 52" | 42" |
| CUTTING HEIGHTS | 1.5"-4.5" | 1.5"-4.5" | 1.5"-4.5" |
| CUTTING POSITIONS | 13 | 13 | 13 |
| WHEELS | | | |
| FRONT AXLE | Fixed | Fixed | Fixed |
| FRONT | II x 4-5 | II x 4-5 | II x 4-5 |
| REAR | 18x 8.5 | 18x 8.5 | 18x 8.5 |
| FEATURES | | | |
| SEAT | Plush High Back w/ seat springs, lever adjust, arm rests | Plush High Back w/ seat springs, lever adjust, arm rests | Plush High Back w/ seat springs, lever adjust, arm re |
| HOUR METER | Standard | Standard | Standard |
| WARRANTY | | | |
| UNIT | 3 Year Limited Consumer | 3 Year Limited Consumer | 3 Year Limited Consumer |
| DECK SHELL & FRAME | 5 Year Limited Deck Shell & Frame | 5 Year Limited Deck Shell & Frame | 5 Year Limited Deck Shell & Frame |
| MACHINE DIMENSIONS | | | |
| WEIGHT (lbs) | 605 | 635 | TBD |
| LENGTH | 77.5" | 77.5" | 77.5" |
| WIDTH | 54.2" | 63.4" | TBD |
| *************************************** | | 40.9" | 40.9" |

Registered trademark and ""trademark of Ariens Company, Kawasaki", Kohler" and Hydro-Gear" are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visitariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2016 Ariens Company. All rights reserved.

An Ariens Company Brand