



# PE-401 3HPWSCAT-HWTB

## HONDA GX390, 4000 PSI

POWERED by  
**HONDA**



### SPECIFICATIONS

STAINLESS STEEL FRAME

PART#	GPM	PSI	DISPLACEMENT	TRIPLEX PUMP	UNLOADER
PE-4013HWPSCAT-HWTB	4.0	4000	389cc HONDA GX390	CAT 66DX40GG1	EXTERNAL

#### ACCESSORIES INCLUDED

PART #	DESCRIPTION
2 x 85.238.153	3/8" 50' HIGH PRESSURE STEEL BRAIDED HOSE
85.205.026	WAND ASSEMBLY WITH GUN AND COUPLER
85.210.040BEP	#4 QUICK CONNECT NOZZLES: 0°, 15°, 40°, SOAPER
85.206.018L	18" STANDARD FIBERGLASS TELESCOPING WAND
85.403.007	20" WHIRL-A-WAY
85.300.044	BALL VALVE KIT

#### ADDITIONAL INFO

- LOW PRESSURE CHEMICAL INJECTOR
- STAINLESS STEEL FRAME **PART# 85.600.078**
- 13" PNEUMATIC TIRES **PART# 85.660.036**
- ENGINE OIL 10W 30 **PART# 85.490.002**
- PUMP OIL 30W NON DETERGENT **PART# 85.490.000**
- 1" KEYED SHAFT

#### PUMP OPTIONS


CAT 66DX40GG1  
85.119.025B  
REPLACEMENT UNLOADER  
85.300.037



#### SHIPPING



26 IN



ENGINE  
WARRANTY

PUMP  
WARRANTY

