

Cam Spray Model MCB5055H MCB Series Oil Fired Hot Water Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Adjustable pressure
- Adjustable thermostat
- Pressure pop-off
- Chemical injection standard on 2000-5000 PSI models
- Powder coated 1 inch square steel tube frame (U.S. Manufactured)
- Easily replaceable schedule 80 coil with stainless cold wrap on 2000-4000 PSI models (U.S. manufactured)
- Unit is a skid style; no electricity required, equipped with a 12 volt oil fired burner
- Group 24 Battery not included
- Unit can be operated as either a cold water only or hot water unit
- Wet steam option available: Call for Pricing
- Look for optional accessories like the swivel hose reel (526496.KIT) that mounts to the frame
- Assembled in USA
- **All hot water machines must be properly vented if operated indoors**



Product Specifications:

- Operating Pressure in psi/bar : 5000 / 345
- Flow Rate in gpm/lpm : 5.5 / 20.9
- Engine Displacement: 688 cc
- Engine Manufacturer: Honda GX Electric Start
- Engine Fuel Tank Capacity: 5 gallon
- Maximum Pump Inlet Water Temperature: 140° F
- Pump Thermal Protection : Mechanical
- Hose Dimension : 50' x 3/8"
- Trigger gun with w6" wand with interchangeable pressure nozzles in 0°, 15°, 25°, 40° and soap tip
- Burner Fuel Type: #1, #2 Diesel, Kerosene or JP8
- Burner Fuel Tank Capacity : 9 gallon
- Product Dimension: 42" L x 35" W x 45" H
- Ship Weight : 700 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com