

Cam Spray Model 3000WM/SS Wall Mount Series Electric Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Adjustable pressure
- Adjustable dual chemical injection with 10' chemical hoses
- Heavy duty totally enclosed fan cooled motor (U.S. manufactured)
- Powder coat frame with wand/hose rack on WM models
- Stainless Steel frame with wand/hose rack on WM/SS models
- Assembled in USA



Product Specifications:

- Operating Pressure in psi/bar : 3000 / 207
- Flow Rate in gpm/lpm : 4 / 15.2
- Horsepower : 7.5
- Voltage/Amperage/Phase : 230 volt / 34 Amp / 1 ph
- Power Cord : 10' to be wired directly into circuit protected by a GFCI breaker
- Maximum Pump Inlet Water Temperature : 160° F
- Pump Thermal Protection : Mechanical
- Hose Dimension : 50' x 3/8"
- Gun/Wand/Tip: Trigger gun/dual wand with side handle and detergent tip with interchangeable pressure nozzles in 0°, 15°, 25° and 40°
- Product Dimension: 28" L x 22" W x 30" H
- Ship Weight : 260 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com