



**GR3100
GR3200
GR3300**

3-in-1 AIR COMPRESSOR/GENERATOR/WELDER



Two Stage Cast Iron Air Compressor

Provides high output and industrial reliability



50-200 Amp DC Welder

Welds up to 1/2 inch steel



**5000 Watt Generator with
U/L & OSHA Compliant Control Panel and GFCI Protection**

Power for jobsite needs; offers safe interaction



Ideal for commercial and industrial applications on the job-site and mobile services. Great for service providers and maintenance departments.

Features (2) 120V 20 Amp Duplex Outlets (NEMA 5-20R) and (1) 120/240V 30 Amp Twistlock (NEMA L14-30R)



**GR3200
30 Gallon Tank**



GR3300 - Tankless
Includes 2 Gallon Accumulator Tank - enables quick, easy hook up to remote tank

Specifications

GENERATOR

Output	Type	Watts	Volts
AC	Brush	6000 Surge/ 5000 Continuous	120V & 240V

AIR COMPRESSOR

Type	CFM @ 90 PSI	CFM @ 175 PSI	Air Tank	Max PSI	Air Rail
Reciprocating 2-Stage	14.3	13.7	GR3100 -10 Gal. (twin 5 Gal.) GR3200 - 30 Gal. GR3300 - Tankless	175	3/8 in. NPT - High Flow

WELDER

Amps	Duty Cycle	Material Thickness
50-200 Amp DC	100%@150A / 65%@180A	16 gauge to 1/2 in. steel

ENGINE

Brand	Model Number	Cylinders	Start	Throttle	Fuel Type	Fuel Capacity
Honda	GX390	Single	Electric	Auto-Idle	Gas	6.4 US Quarts

DIMENSIONS

Model	Length	Width	Height	Weight	UPC Code
GR3100 Assembled	49 in.	23 in.	28.5	485 lbs.	045564637187
GR3100 Shipping	49.8 in.	26 in.	34.5	522 lbs.	
GR3200 Assembled	49 in.	23 in.	42 in.	554 lbs.	045564 637637
GR3200 Shipping	49.8 in.	30 in.	48 in.	591 lbs.	
GR3300 Assembled	49 in.	23 in.	24 in.	431 lbs.	045564 637644
GR3300 Shipping	49.8 in.	26 in.	30 in.	468 lbs.	

Note: 12V power source for starting and welding cables not included

GR 3-n-1 Series_0913