## **DIXIE CHOPPER**。

## STRYKER STAND-ON

**MODELS:** 

**2648** 26hp, 48" Deck

**2654** 26hp, 54" Deck



## STAND UP FOR SPEED, QUALITY AND RELIABILITY.

Dixie Chopper is proud to introduce the **Stryker Stand-On** series into our commercial line-up. Our newest mower packs a lot of power in a small footprint and features:

- American Muscle The new Vanguard® 810cc series provides power and performance into a heavy-duty 26 horsepower engine.
- **Compact Stand-On Design** The Stryker's small footprint allows it to fit through narrow gates and take up less trailer space.
- **Industrial Strength** Forged from 7-gauge steel and 14-gauge stainless steel, the Stryker is built for the rigors of commercial mowing.
- Versatile Design Flip up the operator platform to use the Stryker as a conventional walk-behind, giving you more mowing options.
- **Deeper Deck** The large V6 deck features 7-gauge steel and can easily handle large volumes of grass without slowing you down.
- **Built-In Footsteps** Allows you to shift weight balance for better traction along hillsides.



Vanguard® Engine – 26 horsepower commercial engine.



**OCDC** – Open and close the discharge chute on command.



**Hydro-Gear® ZT-3400** – Commercialgrade transmission with serviceable filter.



**Heavy-Duty Spindles** – Tried and true design for over 25 years.



**48"/54" V6 Cutting System** – Deeper deck for cutting through thick grass.



\*up to 500 hour limited warranty

<sup>\*</sup>Actual production model may vary



	48" Deck	54" Deck	
Model	2648	2654	
Engine			
Manufacturer	Vanguard®		
Horsepower	26		
Displacement	810cc		
Air-cleaner	2 stage		
Cooling	Air cooled		
Starter	Electric		
Engine warranty	3 Year		

Drive System		
Dual Hydrostatic	Hydro-Gear® ZT-3400	
Ground speed	8 mph	
Parking brake	Integrated in transmission	

Mower Deck		
Deck size	48"	54"
Acres/hour	3.1	3.7
Cutting height	1.5" - 5"	
<b>OCDC</b> (operator controlled discharge chute)	Standard	
Deck height adjustments	Manual lift, 1/4" increments	
Electric lift	Optional	
Deck engagement	Ogura® 150 ft-lbs	
Construction	7 ga formed & welded	
Top plate	7 ga bolted (not welded)	
Blades	3 - 17.875" x 2.5"	3 - 21.375" x 2.5"
Blade tip speed (approximate)	17,875 fpm	17,399 fpm
Spindle housings	1pc keyless sealed cast iron	
Spindles	1.25" Effective diameter machined shaft	
Anti-scalp rollers	4	
Pulleys	Vented split 3/16" steel deep groove	

General		
Battery	12 Volt, 300cca	
Digital display	Tachometer, voltmeter, service alerts	
Fuel capacity	6 gallons	
Rear tires	23 x 9.5-12 Grass Master	23 x 10.5-12 Grass Master
Front tires	15 x 6-8	
Frame	Welded 2 x 2 tube, 7 ga formed	
Operator Platform	Flip-up, steel	
Springer forks	Optional	

Dimensions				
Overall height	48"			
Overall width (with chute up)	49"	55"		
Overall width (with chute)	64"	70"		
Overall length	67.5"			
Overall length (platform down)	79"			
Weight	824 lbs	844 lbs		

