

Specifications

	PREMIER	PRO	PRO-XL
Engine	Briggs & Stratton (See Engine Owner's Manual for Engine Specifications)	Briggs & Stratton (See Engine Owner's Manual for Engine Specifications)	Briggs & Stratton (See Engine Owner's Manual for Engine Specifications)
BATTERY			
	N/A	12V, 9 Ah	12V, 9 Ah
BED			
Capacity - Volume (Cu Ft)	5.2	8	8
Capacity - Weight (Lbs)	500	700	800
Bed Height (In)	20	20	20
Construction	High-Density Polyethylene (Hdpe)	Cellular Core High Strength Molded Polyethylene	Cellular Core High Strength Molded Polyethylene
Dump Angle (Degrees)	60°	60°	60°
Latch Mechism	Intergrated Latch & Handle	Intergrated Latch & Handle	N/A (Actuator Latches The Bed)
TRANSMISSION			
Speeds	Forward 3: 3.7 Mph Forward 2: 2.4 Mph Forward 1: 1.3 Mph Reverse: 1.4 Mph	Forward 3: 3.7 Mph Forward 2: 2.4 Mph Forward 1: 1.3 Mph Reverse: 1.4 Mph	Forward 3: 3.7 Mph Forward 2: 2.4 Mph Forward 1: 1.3 Mph Reverse: 1.4 Mph
Brake	Transaxle Disc Brake	Transaxle Disc Brake	Transaxle Disc Brake
FRAME			
Frame Type	Tubular Steel (1.5" Diameter X 12 Ga Thick)	Tubular Steel (1.5" Diameter X 12 Ga Thick)	Tubular Steel (1.5" Diameter X 12 Ga Thick)
Skid Plate	9 Ga Thick	9 Ga Thick	9 Ga Thick
Handlebar Height (In)	37	37	37
ACTUATOR			
Included	N/A	N/A	Yes
Full Load Speed (Mm/S (In/S))	N/A	N/A	12 (0.47)
Full Load Seconds/Lift	N/A	N/A	16.745
No Load Speed (Mm/S (In/S))	N/A	N/A	20 (0.79)
No Load Seconds/Lift	N/A	N/A	9.962
Stroke (Mm (In))	N/A	N/A	200 (7.87)
Duty Cycle	N/A	N/A	10% (Approximately 1 Full Capacity Load Every 4.5 Minutes)
Enclosure Rating	N/A	N/A	IP65
WHEELS			
Front (Size & Type)	16" Diameter, 4" Width, Snowhog Tread	16" Diameter, 4" Width, Snowhog Tread	16" Diameter, 4" Width, Snowhog Tread
Rear (Size & Type)	11" Diameter, 4" Width, Rib	11" Diameter, 4" Width, Rib	11" Diameter, 4" Width, Rib
DIMENSIONS			
Overall Product Dim's	66.5 L X 33.25 W X 41 H	63.25 L X 34.5 W X 41 H	63.25 L X 34.5 W X 41 H
Product Weight	184	231	240
Ground Clearance	2"	2"	2"