

**POWERED CHORE EQUIPMENT** 

23275

## **EDGER**

## **Edger & Lightweight Trimming Tool**

with 99cc 4-Cycle Viper® Engine



Reclaim your yard with the Earthquake® Edger. A strong, 99cc Viper® engine powers the unit through the toughest weed encroachments, while the 4-wheel design provides stable control for clean and straight lines. The Edger's ergonomic handlebars feature a tool holder for convenient access to hand tools. For optimum safety, the centrifugal clutch stops the blade the moment the throttle is released. Durable chain skirting protects the operator from flying debris. Add definition to your outdoor space with the powerful and reliable Earthquake® Edger.

## FEATURES AND BENEFITS

**HANDLEBAR** - Industry-first accessory tool holder for convenient lawn detailing.

**POWERFUL** - 99cc Viper® Engine with centrifugal clutch.

**CHAIN DEBRIS GUARD** - Protects operator from flying debris.

**PIVOTING HEAD** - Allows for multiple edging and cutting angles.



## **SPECIFICATIONS**

ENGINE TYPE         4-CYCLE           ENGINE TYPE         3.5 FT-LB @ 2500 RPM           FUEL TYPE         87+ OCTANE UNLEADED GASOLINE           STARTING SYSTEM         RECOIL           CYLINDER CONFIGURATION         HORIZONTAL           CYLINDER MATERIAL         ALUMINUM           FLYWHEEL         CAST ALUMINUM           FUEL CAPACITY (GAL)         0.53           DISPLACEMENT (CC)         99           FUEL TANK         STEEL           TRANSLUCENT FUEL TANK         NO           THROTTLE CONTROL         ROTARY ON ENGINE           COMPRESSION RELIEF VALVE         NO           MUFFLER GUARD         NO           ON/OFF SWITCH         HIGH PROFILE ROCKER           RECOMMENDED OIL         10W-30           LOW OIL SHUTDOWN         NO           SPARK PLUG         EST           CERTIFICATIONS         EPA III, CARB           DRIVE SYSTEM         BELT           ANSI B71.8-1996         YES           HANDLEBAR STYLE         BICYCLE WITH FORM GRIPS           MULTIPLE HEIGHT POSITIONS         2           OPERATION         TWO-HANDED           SELF PROPELLED         NO           EDGER BLADE (MATERIAL)         SPRING STEEL		
ENGINE TORQUE (FT-LB)         3.5 FT-LB @ 2500 RPM           FUEL TYPE         87+ OCTANE UNLEADED GASOLINE           STARTING SYSTEM         RECOIL           CYLINDER CONFIGURATION         HORIZONTAL           CYLINDER MATERIAL         ALUMINUM           FLYWHEEL         CAST ALUMINUM           FUEL CAPACITY (GAL)         0.53           DISPLACEMENT (CC)         99           FUEL TANK         STEEL           TRANSLUCENT FUEL TANK         NO           THROTTLE CONTROL         ROTARY ON ENGINE           COMPRESSION RELIEF VALVE         NO           MUFFLER GUARD         NO           ON/OFF SWITCH         HIGH PROFILE ROCKER           RECOMMENDED OIL         100W-30           LOW OIL SHUTDOWN         NO           SPARK PLUG         ESTC           CERTIFICATIONS         EPA III, CARB           DRIVE SYSTEM         BELT           ANSI B71.8-1996         YES           HANDLEBAR STYLE         BICYCLE WITH FORM GRIPS           MULTIPLE HEIGHT POSITIONS         2           OPERATION         TWO-HANDED           SELF PROPELLED         NO           EDGING DEPTH (IN)         3.5           EDGER BLADE (MATERIAL)         SPRING STEEL<	ENGINE BRAND	VIPER®
FUEL TYPE         87+ OCTANE UNLEADED GASOLINE           STARTING SYSTEM         RECOIL           CYLINDER CONFIGURATION         HORIZONTAL           CYLINDER MATERIAL         ALUMINUM           FLYWHEEL         CAST ALUMINUM           FUEL CAPACITY (GAL)         0.53           DISPLACEMENT (CC)         99           FUEL TANK         STEEL           TRANSLUCENT FUEL TANK         NO           THROTTLE CONTROL         ROTARY ON ENGINE           COMPRESSION RELIEF VALVE         NO           MUFFLER GUARD         NO           ON/OFF SWITCH         HIGH PROFILE ROCKER           RECOMMENDED OIL         10W-30           LOW OIL SHUTDOWN         NO           SPARK PLUG         E5TC           CERTIFICATIONS         EPA III, CARB           DRIVE SYSTEM         BELT           ANSI B71.8-1996         YES           HANDLEBAR STYLE         BICYCLE WITH FORM GRIPS           MULTIPLE HEIGHT POSITIONS         2           OPERATION         TWO-HANDED           SELF PROPELLED         NO           EDGER BLADE (MATERIAL)         SPRING STEEL           EDGER BLADE (MATERIAL)         SPRING STEEL           EDGER BLADE (RPM)         3400	ENGINE TYPE	4-CYCLE
STARTING SYSTEM RECOIL CYLINDER CONFIGURATION HORIZONTAL CYLINDER MATERIAL ALUMINUM FLYWHEEL CAST ALUMINUM FUEL CAPACITY (GAL)	ENGINE TORQUE (FT-LB)	3.5 FT-LB @ 2500 RPM
CYLINDER CONFIGURATION HORIZONTAL CYLINDER MATERIAL ALUMINUM FLYWHEEL CAST ALUMINUM FUEL CAPACITY (GAL) 0.53 DISPLACEMENT (CC) 99 FUEL TANK STEEL TRANSLUCENT FUEL TANK NO THROTTLE CONTROL ROTARY ON ENGINE COMPRESSION RELIEF VALVE NO MUFFLER GUARD NO ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG ESTC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	FUEL TYPE	87+ OCTANE UNLEADED GASOLINE
CYLINDER MATERIAL ALUMINUM FLYWHEEL CAST ALUMINUM FUEL CAPACITY (GAL) 0.53 DISPLACEMENT (CC) 99 FUEL TANK STEEL TRANSLUCENT FUEL TANK NO THROTTLE CONTROL ROTARY ON ENGINE COMPRESSION RELIEF VALVE NO MUFFLER GUARD NO ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	STARTING SYSTEM	RECOIL
FLYWHEEL CAPACITY (GAL) 0.53  DISPLACEMENT (CC) 99  FUEL TANK STEEL  TRANSLUCENT FUEL TANK NO  THROTTLE CONTROL ROTARY ON ENGINE  COMPRESSION RELIEF VALVE NO  MUFFLER GUARD NO  ON/OFF SWITCH HIGH PROFILE ROCKER  RECOMMENDED OIL 10W-30  LOW OIL SHUTDOWN NO  SPARK PLUG E5TC  CERTIFICATIONS EPA III, CARB  DRIVE SYSTEM BELT  ANSI B71.8-1996 YES  HANDLEBAR STYLE BICYCLE WITH FORM GRIPS  MULTIPLE HEIGHT POSITIONS 2  OPERATION TWO-HANDED  SELF PROPELLED NO  EDGING DEPTH (IN) 3.5  EDGER BLADE (MATERIAL) SPRING STEEL  EDGER BLADE (RPM) 3400  WHEEL DIAMETER (IN) 7.5, 6.5	CYLINDER CONFIGURATION	HORIZONTAL
FUEL CAPACITY (GAL)  DISPLACEMENT (CC)  P99  FUEL TANK  STEEL  TRANSLUCENT FUEL TANK  NO  THROTTLE CONTROL  ROTARY ON ENGINE  COMPRESSION RELIEF VALVE  NO  MUFFLER GUARD  NO  ON/OFF SWITCH  RECOMMENDED OIL  LOW OIL SHUTDOWN  SPARK PLUG  CERTIFICATIONS  EPA III, CARB  DRIVE SYSTEM  BELT  ANSI B71.8-1996  YES  HANDLEBAR STYLE  BICYCLE WITH FORM GRIPS  MULTIPLE HEIGHT POSITIONS  2  OPERATION  TWO-HANDED  SELF PROPELLED  NO  EDGING DEPTH (IN)  3.5  EDGER BLADE (MATERIAL)  SPRING STEEL  EDGER BLADE (RPM)  3400  WHEEL DIAMETER (IN)  7.5, 6.5	CYLINDER MATERIAL	ALUMINUM
DISPLACEMENT (CC) 99 FUEL TANK STEEL TRANSLUCENT FUEL TANK NO THROTTLE CONTROL ROTARY ON ENGINE COMPRESSION RELIEF VALVE NO MUFFLER GUARD NO ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	FLYWHEEL	CAST ALUMINUM
FUEL TANK STEEL TRANSLUCENT FUEL TANK NO THROTTLE CONTROL ROTARY ON ENGINE COMPRESSION RELIEF VALVE NO MUFFLER GUARD NO ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	FUEL CAPACITY (GAL)	0.53
TRANSLUCENT FUEL TANK THROTTLE CONTROL ROTARY ON ENGINE COMPRESSION RELIEF VALVE NO MUFFLER GUARD NO ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	DISPLACEMENT (CC)	99
THROTTLE CONTROL ROTARY ON ENGINE COMPRESSION RELIEF VALVE NO MUFFLER GUARD NO ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	FUEL TANK	STEEL
COMPRESSION RELIEF VALVE  MUFFLER GUARD  NO  ON/OFF SWITCH  RECOMMENDED OIL  LOW OIL SHUTDOWN  SPARK PLUG  CERTIFICATIONS  DRIVE SYSTEM  ANSI B71.8-1996  HANDLEBAR STYLE  MULTIPLE HEIGHT POSITIONS  SELF PROPELLED  NO  EDGING DEPTH (IN)  3.5  EDGER BLADE (MATERIAL)  WHEEL DIAMETER (IN)  NO  NO  NO  NO  NO  NO  NO  EDGING DEPTH (IN)  3400  WHEEL DIAMETER (IN)  7.5, 6.5	TRANSLUCENT FUEL TANK	NO
MUFFLER GUARD  ON/OFF SWITCH  RECOMMENDED OIL  LOW OIL SHUTDOWN  SPARK PLUG  CERTIFICATIONS  DRIVE SYSTEM  ANSI B71.8-1996  HANDLEBAR STYLE  MULTIPLE HEIGHT POSITIONS  SELF PROPELLED  NO  EDGING DEPTH (IN)  SOURCE SYSTEM  SPRING STEEL  EDGER BLADE (MATERIAL)  WHEEL DIAMETER (IN)  NO  10W-30  10W-30  10W-30  EDGING PROFILE ROCKER  RECOMMENDED SET 10W-30  HIGH PROFILE ROCKER  BOW-30  BELT  10W-30  EDGING DEPTH (IN)  3.5	THROTTLE CONTROL	ROTARY ON ENGINE
ON/OFF SWITCH HIGH PROFILE ROCKER RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	COMPRESSION RELIEF VALVE	NO
RECOMMENDED OIL 10W-30 LOW OIL SHUTDOWN NO SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	MUFFLER GUARD	NO
LOW OIL SHUTDOWN  SPARK PLUG  SPARK PLUG  CERTIFICATIONS  EPA III, CARB  DRIVE SYSTEM  BELT  ANSI B71.8-1996  YES  HANDLEBAR STYLE  BICYCLE WITH FORM GRIPS  MULTIPLE HEIGHT POSITIONS  2  OPERATION  TWO-HANDED  SELF PROPELLED  NO  EDGING DEPTH (IN)  3.5  EDGER BLADE (MATERIAL)  SPRING STEEL  EDGER BLADE (RPM)  WHEEL DIAMETER (IN)  7.5, 6.5	ON/OFF SWITCH	HIGH PROFILE ROCKER
SPARK PLUG E5TC CERTIFICATIONS EPA III, CARB DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	RECOMMENDED OIL	10W-30
CERTIFICATIONS  DRIVE SYSTEM  BELT  ANSI B71.8-1996  YES  HANDLEBAR STYLE  BICYCLE WITH FORM GRIPS  MULTIPLE HEIGHT POSITIONS  OPERATION  TWO-HANDED  SELF PROPELLED  NO  EDGING DEPTH (IN)  3.5  EDGER BLADE (MATERIAL)  SPRING STEEL  EDGER BLADE (RPM)  3400  WHEEL DIAMETER (IN)  7.5, 6.5	LOW OIL SHUTDOWN	NO
DRIVE SYSTEM BELT ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2 OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	SPARK PLUG	E5TC
ANSI B71.8-1996 YES HANDLEBAR STYLE BICYCLE WITH FORM GRIPS MULTIPLE HEIGHT POSITIONS 2  OPERATION TWO-HANDED  SELF PROPELLED NO  EDGING DEPTH (IN) 3.5  EDGER BLADE (MATERIAL) SPRING STEEL  EDGER BLADE (RPM) 3400  WHEEL DIAMETER (IN) 7.5, 6.5	CERTIFICATIONS	EPA III, CARB
HANDLEBAR STYLE  MULTIPLE HEIGHT POSITIONS  2  OPERATION  TWO-HANDED  SELF PROPELLED  NO  EDGING DEPTH (IN)  3.5  EDGER BLADE (MATERIAL)  SPRING STEEL  EDGER BLADE (RPM)  WHEEL DIAMETER (IN)  7.5, 6.5	DRIVE SYSTEM	BELT
MULTIPLE HEIGHT POSITIONS 2  OPERATION TWO-HANDED  SELF PROPELLED NO  EDGING DEPTH (IN) 3.5  EDGER BLADE (MATERIAL) SPRING STEEL  EDGER BLADE (RPM) 3400  WHEEL DIAMETER (IN) 7.5, 6.5	ANSI B71.8-1996	YES
OPERATION TWO-HANDED SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	HANDLEBAR STYLE	BICYCLE WITH FORM GRIPS
SELF PROPELLED NO EDGING DEPTH (IN) 3.5 EDGER BLADE (MATERIAL) SPRING STEEL EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	MULTIPLE HEIGHT POSITIONS	2
EDGING DEPTH (IN) 3.5  EDGER BLADE (MATERIAL) SPRING STEEL  EDGER BLADE (RPM) 3400  WHEEL DIAMETER (IN) 7.5, 6.5	OPERATION	TWO-HANDED
EDGER BLADE (MATERIAL)  EDGER BLADE (RPM)  WHEEL DIAMETER (IN)  7.5, 6.5	SELF PROPELLED	NO
EDGER BLADE (RPM) 3400 WHEEL DIAMETER (IN) 7.5, 6.5	EDGING DEPTH (IN)	3.5
WHEEL DIAMETER (IN) 7.5, 6.5	EDGER BLADE (MATERIAL)	SPRING STEEL
	EDGER BLADE (RPM)	3400
WHEEL WIDTH (IN) 2	WHEEL DIAMETER (IN)	7.5, 6.5
	WHEEL WIDTH (IN)	2

WHEEL MATERIAL	PLASTIC HUB / RUBBER TIRE
LABELING	PICTOGRAM / EN
MODEL BRAND	EARTHQUAKE®
EXCLUDED STATES	CALIFORNIA
ILLUSTRATED PARTS LIST	MANUAL, ONLINE
MANUAL LANGUAGE	ENGLISH
ASSEMBLED DIMENSIONS (IN)	38.7 X 19.2 X 37.7
PACKAGED DIMENSIONS (IN)	23.8 X 29.76 X 21.3
NET WEIGHT (LB)	-
GROSS WEIGHT (LB)	-
CARTON STYLE	STENCIL BROWN BOX
PALLET QTY	-
40' HC CONTAINER QTY	350 UNITS
UPC CODE	012642 004315
WARRANTY	EDGER 5 YEAR, ENGINE 5 YEAR

All weights, specifications and features are approximate and are subject to change without notice. Due to continuous product improvements, product images may not be exact. Warning labels in some product images may have been removed for photography purposes only. Props shown in photos not included. Some assembly may be required.



Ardisam is an American company based in the heart of the Midwest, where the Seasons help shape the character of who we are and the products we build. Because we believe in and use the many products we design, we are uniquely qualified to deliver genuine innovation and service that are born of the outdoor rural lifestyle in which we live. Spring, Summer, Winter, or Fall, we are always prepared to serve the needs of our customers through the best designed products on the market, as well as through our world class customer service. Since 1960, Ardisam has built its legacy on the tradition of providing countless customers with exceptional service and value through its many brands that span all Seasons and stand the test of time.