

WANDS




WAN-SLH

Zinc coated, molded grip.
 1/4" Male pipe thread.
 Also available in stainless steel.
 Rated at 300°F



| | |
|------------------|---|
| WAN-SLH | SIDE HANDLE GRIP FOR 1/4" PIPE WAND |
| WAN-SL12 | 12" INSULATED SINGLE LANCE |
| WAN-SL24 | 24" INSULATED SINGLE LANCE |
| WAN-SL36 | 36" INSULATED SINGLE LANCE |
| WAN-SL48 | 48" INSULATED SINGLE LANCE |
| WAN-SL36-SS | 36" INSULATED SINGLE LANCE, STAINLESS STEEL |
| WAN-SL40SS-12 | 40" SINGLE LANCE, STAINLESS STEEL, 1/2" MNPT |
| WAN-SL59 | 59" INSULATED SINGLE LANCE |
| WAN-SL79 | 79" INSULATED SINGLE LANCE |
| WAN-SL48SS-SH-12 | 48" SINGLE LANCE C/W SIDE HANDLE, STAINLESS STEEL |

GUN/WAND/QUICK COUPLER ASSEMBLY



KIT-GW36

Complete assembly for pressure washing. Quick attach for quick assembly with the GUN-TG5010 or GUN-TG5010V. Rated at 10 GPM @ 5000 PSI. (Add "V" to upgrade to Vega Gun)

| | |
|-----------|--|
| KIT-GW12 | KIT - 5000 PSI GUN, 12" WAND, QC & NIPPLE |
| KIT-GW24 | KIT - 5000 PSI GUN, 24" WAND, QC & NIPPLE |
| GUN-GW36 | KIT - 4000 PSI GUN, 36" WAND, QC & NIPPLE |
| KIT-GW36V | KIT - 5000 PSI VEGA GUN, 36" WAND, QC & NIPPLE |
| GUN-GW48 | KIT - 5000 PSI GUN, 48" WAND, QC & NIPPLE |
| KIT-GW59 | KIT - 5000 PSI GUN, 59" WAND, QC & NIPPLE |
| KIT-GW79 | KIT - 5000 PSI GUN, 79" WAND, QC & NIPPLE |

O-RINGS



1/4"

3/8"

O-Rings for AP, Hansen, Foster, Parker, and other quick-coupler brands. Viton to 300°F

| | |
|------------|---------------------|
| ORG-QC14HT | QC, 1/4", HIGH TEMP |
| ORG-QC38HT | QC, 3/8", HIGH TEMP |
| ORG-QC12HT | QC, 1/2", HIGH TEMP |

HARNESS



Used with extension wands to help stabilize and support the wand for ease of use.

| | |
|---|--------------|
| WAN-HRNS | SUPPORT BELT |
| IT IS RECOMMENDED TO PAIR THIS ITEM WITH THE EXTENSION WANDS FOR SAFETY & CONTROL | |

STEAM WAND



WAN-STM

Must be used in steam application. Safety guard around wand.

GUN-STM12-38SW

| | |
|-----------------|--|
| GUN-STM12-38 SW | STEAM TRIGGER GUN. 0 GPM @ 1500 PSI & 350°. INLET: 1/2" FPT OUTLET: 3/8" FPT DUE TO LIABILITY WE DO NOT INSTALL ON STEAM SYSTEMS |
| WAN-STM38 | 3/8" STEAM WAND WITH EXPANDED METAL GRIP |
| WAN-STM12 | 1/2" STEAM WAND WITH EXPANDED METAL GRIP |
| WAN-STM34 | 3/4" STEAM WAND WITH EXPANDED METAL GRIP |
| WAN-STM1 | 1" STEAM WAND WITH EXPANDED METAL GRIP |

BRASS QUICK COUPLERS



For speedy and sturdy interchanging of tools and attachments. Disconnect coupler band rated at 5000 PSI, 210°F

STANDARD QUICK COUPLER

| | |
|-------------|-----------------------|
| FIT-QC14F/M | 1/4" FNPT/MNPT, BRASS |
| FIT-QC38F/M | 3/8" FNPT/MNPT, BRASS |
| FIT-QC12F/M | 1/2" FNPT/MNPT, BRASS |

STANDARD QUICK COUPLER NIPPLES

| | |
|--------------|-----------------------|
| FIT-QCN14F/M | 1/4" FNPT/MNPT, BRASS |
| FIT-QCN38F/M | 3/8" FNPT/MNPT, BRASS |
| FIT-QCN12F/M | 1/2" FNPT/MNPT, BRASS |

STAINLESS STEEL QUICK COUPLERS



For speedy and sturdy interchanging of tools and attachments. Disconnect coupler band rated at 5000 PSI, 210°F

STAINLESS STEEL QUICK COUPLER

| | |
|----------------|--|
| FIT-QC14F/M-SS | 1/4" FNPT/MNPT, STAINLESS STEEL |
| FIT-QC38F/M-SS | 3/8" FNPT/MNPT, STAINLESS STEEL |
| FIT-QC12F/M-SS | 1/2" FNPT/MNPT, STAINLESS STEEL |
| FIT-QC12F-SS-L | 1/2" FNPT, STAINLESS STEEL, LOCKING TYPE |

STAINLESS STEEL QUICK COUPLER NIPPLES

| | |
|-----------------|--|
| FIT-QCN14F/M-SS | 1/4" FNPT/MNPT, STAINLESS STEEL |
| FIT-QCN38F/M-SS | 3/8" FNPT/MNPT, STAINLESS STEEL |
| FIT-QCN12F/M-SS | 1/2" FNPT/MNPT, STAINLESS STEEL |
| FIT-QCN12F-SS-L | 1/2" FNPT, STAINLESS STEEL, LOCKING TYPE |

FITTINGS



| | |
|--------------|--|
| FIT-S1003-B | HEX COUPLING, 1/4", FNPT |
| FIT-S1022-C | HEX NIPPLE, 3/8", STEEL (WMM0003GS) |
| FIT-S1022-CB | HEX NIPPLE, REDUCING, 3/8" X 1/4", STEEL (WMM0302GS) |
| FIT-S1022-D | HEX NIPPLE, 1/2", STEEL (WMM0004GS) |
| FIT-S1022-DB | HEX NIPPLE, REDUCING, 1/2" X 1/4", STEEL (RCF0402SS) |
| FIT-S1022-DC | HEX NIPPLE, REDUCING, 1/2" X 3/8", STEEL (WMM0403GS) |
| FIT-S1022-EC | HEX NIPPLE, REDUCING, 3/4" X 3/8", STEEL |

EXTENSION WANDS




WAN-TS24HD

Two sizes to choose from, high quality telescoping wand reaches either 18' or 24' at max length. Lightweight and balanced under pressure for various spray patterns. Up to 10 GPM @ 4000 PSI @ 195° F

| | |
|------------|---------------------|
| WAN-TS18HD | 18', EXTENSION WAND |
| WAN-TS24HD | 24', EXTENSION WAND |

DUAL LANCE WANDS



WAN-DL38SN

Controls soap at handle for low pressure application.

| | |
|---------------------------------------|-------------------------------------|
| WAN-DL38SN | 36", WITH KNOB & SOAP NOZZLE |
| WAN-DL38SN-SH | 36", WITH SIDE HANDLE & SOAP NOZZLE |
| NOZZLE 1/4" TIP EXTRA - HIGH PRESSURE | |
| SPECIFY PSI & GPM | |