

EASY-KLEEN

PRESSURE SYSTEMS LTD.

MANUFACTURER OF HIGH PRESSURE CLEANING EQUIPMENT

Portable Pickup Truck Skid

The Easy Kleen Portable Pickup Skid Unit is designed to fit into a 6'6" box of a pickup truck.

Model Specifications:

MODEL	GPM	PSI	BTU	HP/ Engine	Fuel	DRIVE	ELECTRIC START	BURNER
EZO3504G-K-PSR	4	3500	400,000	14 KOHLER	Gasoline	GEARBOX	YES	12V
EZO3504D-K-PSR	4	3500	400,000	9.8 KOHLER	Diesel	GEARBOX	YES	12V

Startup:

1. Ensure all ball valves are closed prior to starting machine.
2. Fill 225 gallon tank with water. NOTE: This tank can only be used with polyethylene compatible liquids.
3. Open ball valve for main water supply from tank, then start pump. Follow the rest of the instructions in the pressure washer user manual.

Special Winterization Instructions:

Use this procedure if machine is to be transported, stored, or operated in winter conditions to prevent damage from freezing.

1. Close ball valve for the main water supply to pump from water tank.
2. Open Dump Valve to drain excess water from 225 gallon water tank.
3. Fill the 10 gallon antifreeze tank with full strength, winter rated, vehicle windshield washing fluid or Anti-Freeze, **RATED FOR MINIMUM -40°C**.
4. Ensure pressure wand assembly is properly connected, then open ball valve below antifreeze tank to run antifreeze through the system.

5. Start pump and engage trigger on the pressure gun. Operate the system until fluid coming out from the nozzle runs the same color as antifreeze fluid. Release trigger with pump still running, and wait 10 seconds to allow antifreeze to pass through bypass hose before shutting off pump. Your machine is now prepared for storage.

Component Identification:

