

NCC199CDV

Next Gen True Commercial Tankless

GQ-C3260WZ-FF US

The rolling update to the NCC199CDV provides industry leading performance for any commercial water heating application. An impressive 10-year heat exchanger warranty comes included, providing businesses with years of hot water without the worry. In addition, the NCC199CDV now eliminates the need to purchase additional accessories by featuring a built-in exhaust non-return valve.

FEATURES

⇒ Built-In Exhaust Non-Return Valve

The new built-in exhaust non-return valve allows for common venting up to 6 heaters.



⇒ 10 Year Commercial Warranty

The NCC199CDV features an industry-leading 10 year heat exchanger warranty.

⇒ Upgraded Stainless Steel Heat Exchangers

Developed with high grade stainless steel, our NCC199CDV comes with 2 heat exchangers that are built to last.

⇒ Energy Saving Efficiency

Combined with a unique negative pressure Venturi gas valve, the NCC199CDV offers a 0.95 UEF, eliminating carbon emissions.



Optional Parts List

Part Name	Part #
Wifi Adapter	NWCC-ADAPTER
Outdoor Vent Cap	VC-6-1
3" Horizontal Hood Termination	PVT-HL
System Controller	SC-401-6M SCU-401-12M (12 unit) SCU-401-24M (24 unit)

SPECIFICATIONS

		NCC199CDV
Weight		70 lbs.
Capacity Range		0.5 - 11.1 GPM (30° F Rise)
Min / Max BTU		18K - 199,900 BTUh
UEF		0.95
Connection Sizes	Water Inlet	NPT 3/4"
	Hot Water Outlet	NPT 3/4"
	Gas Inlet	NPT 3/4"
	Condensate Drain	NPT 1/2"
Water Holding Capacity		0.80 Gallon (3.0 L)
Temperature Settings	°F Mode	100-150°F (In 5°F Intervals) 160°F, 170°F, 185°F (14 options)
	°C Mode	37-48°C (In 1°C Intervals), 50-85°C (In 5°C Intervals) (20 Options)
Operating Pressure		15 - 150 psi (Recommended 50 to 80 psi for maximum performance)
Included Accessories		Remote controller, remote controller cord, anchoring screws, wall mounting bracket