

SPECIFICATIONS

MODEL	DSRM-2600	DSRM-2600U
Length	1841 mm (72.48 in.)	
Width	215 mm (8.46 in.)	669 mm (26.34 in.)
Height	293 mm (11.54 in.)	618 mm (24.33 in.)
Weight (with battery)	5.4 kg (11.9 lb.)	6.1 kg (13.45 lb)
Battery	ECHO eFORCE™ 56V series batteries	
Type	Li-Ion	
Battery voltage	56 (rated 50.4)	
Capacity	See Battery Manual	
Charger type	ECHO eFORCE™ 56V series charger	
Charger input voltage	120V AC 60Hz	
Charging time	See Battery Manual	
Operating Rod	25.0 mm (0.98 in.) aluminum tube	
Drive Shaft	6.15 mm (0.25 in.) flexible shaft	
Cutter Head	Speed Feed® 400 LH nylon line head, line capacity 6.1 m (20 ft.) .095" trimmer line*.	
Rotating Direction	Counterclockwise, viewed from top	
Motor Type	DC / Brushless	
Speed	4860 -9200 RPM	
Gear Case Ratio	1.62	
Charger Lights ○ OFF ● Green blinking ○ OFF ● Green ● Red ○ OFF ● Red ○ OFF ● Red blinking ○ OFF	Green blinking - battery is charging	
	Green - battery is fully charged	
	Red - Battery is too warm. Remove for approximately 30 minutes to cool down	
	Red blinking - Defective battery. Remove and replace with new battery	

* For best unit run time, use .095" Silentwist™ trimmer line. Other .095" line might shorten run time.