



NOTE: UP TO 50% QUIETER THAN MOST RECIPROCATING PISTON COMPRESSORS.

OPERATES AND NORMAL CONVERSATION LEVEL.



+ OPTIONAL SILENT AIR SYSTEM





ESS07V080Z1

***REQUIRES TWO QUALIFYING ANNUAL MAINTENANCE KIT PURCHASES

MAXFLO E250 SERIES

TECH SPECS

MODEL NUMBER:	ESL07V080Z1	ESS07V080Z1
MANUFACTURER:	EMAX	EMAX
TANK SIZE:	80 GALLON	80 GALLON

MOTOR

RUNNING HP:	7.5 HP INDUSTRIAL 1.1 SERVICE FACTOR MOTOR	7.5 HP INDUSTRIAL 1.1 SERVICE FACTOR MOTOR
VOLTAGE:	230	230
MOTOR RPM:	1740	1740
PHASE:	SINGLE	SINGLE
MAGNETIC STARTER:	YES	YES
MOTOR	OPEN DRIP PROOF	OPEN DRIP PROOF
NUMBER OF BELTS	2	2

PUMP

СҒМ	33@100PSI	33@100PSI
	31 @ 175PSI	31 @ 175PSI
PUMP TYPE:	SPLASH LUBRICATED	SPLASH LUBRICATED
RPMS AT MAX	890	890
MAX PRESSURE:	175 PSI	175 PSI
VALVES	REMOVABLE DISC INDUSTRIAL VALVES	REMOVABLE DISC INDUSTRIAL VALVES
RODS	2 - SOLID STEEL	2 - SOLID STEEL
PUMP LIFE (HOURS):	50,000	50,000
EXTENDED LIFETIME PUMP WARRANTY	***OPTIONAL	***OPTIONAL

OVERVIEW

CERTIFICATION:	UL, CSA, ASME	UL, CSA, ASME
DIMENSIONS:	H 71in, W 27in, D 38in	H 71in, W 27in, D 38in
PRODUCT WEIGHT:	804 lbs	830 lbs
WARRANTY:	5 YEAR: 1 YR STD, 4 YR EXTENDED	5 YEAR: 1 YR STD, 4 YR EXTENDED
NOISE LEVEL	CONVERSATION LEVEL	CONVERSATION LEVEL
BELT TENSION ADJUSTER	NO	NO
AUTO DRAIN	NO	NO
CONTINUOUS RUN	NO	NO
1 QT OF AIR COMPRESSOR OIL	YES	YES
VIBRATION ISOLATOR PADS (SET)	YES	YES
AIR SILENCER WITH 5 STAGE FILTRATION	NO	YES
BELT GUARD	16 gauge OSHA Compliant Steel	16 gauge OSHA Compliant Steel