

# LINKTower™

LED LIGHT TOWER

**GENERAC®**  
MOBILE



# LINKTower

## LED LIGHT TOWER

LINKTower from Generac Mobile is a unique portable lighting solution for a wide range of jobs, events and projects, indoors and out. LINKTower provides powerful illumination in a compact, maneuverable design for ultimate versatility and ease of use. Use one, or LINK two towers together, the linking capability allows for flexibility and versatility in lighting events and jobsites. And, because it's powered by a standard 120V outlet, there are no harmful fuel emissions. LINKTower is a clean and safe choice for temporary lighting needs of all kinds.

### SAFE

- Shore-powered LINKTower produces zero localized emissions, so it's safe to use indoors and out

### QUIET

- Silent operation is ideal for music and other special events, and any application in which sound is a concern

### VERSATILE

- Power from 120V utility power source, generator or another light tower
- 120V AC duplex receptacles can power commonly used jobsite tools
- Smaller size and mast design fits through a standard door opening

### COST EFFECTIVE

- Lowest total cost of ownership for a light tower - no service interval, no diesel fuel
- Compact footprint saves on transportation costs
- Instant-on LED lights

### EASY TO USE


- LINKTower can be set up by a single person in less than one minute, saving time and manpower
- Ergonomic folding handles and additional caster wheel allow for one-person maneuverability
- Lockable side access door for internal storage of extension cords and tools
- Forklift pockets and lifting eye ease loading and unloading

## APPLICATIONS

- Music and Special Events
- Industrial Plants
- Manufacturing
- Warehousing
- Worksite Lighting
- Sporting Events
- Parking Lot Lighting
- School Events
- Municipal Projects
- Auto Dealers
- Hi-rise Construction
- Construction
- General Rental



**COMPACT SIZE** fits through a standard doorway




**DURABLE**  
impact-resistant  
fixtures

**LED LIGHTS** are long lasting and efficient; modules and drivers are backed by a 5 year limited warranty

**TWO-HANDLE WINCH** is designed for easy mast deployment; Sets up in one minute

**STABLE** four extendable outriggers designed to withstand 45 mph (72 kph) winds

**MANEUVERABLE** castor wheel enhances improve maneuverability



**LINK TOGETHER**  
TWO LINKTOWERS  
FOR PRECISE AND VERSATILE  
ILLUMINATION

- (1) LINK on a 15A circuit
- (2) LINKs on a 20A circuit

**NEW, MORE  
POWERFUL LEDs;**  
30,528 lumens per  
fixture; 122,112 total  
lumens per tower

**ZERO LOCALIZED  
EMISSIONS** powered  
by standard 120V utility  
shore power

**ADJUSTABLE  
GALVANIZED MAST**  
can be raised up to  
16 feet (4.9 m)

**FOLDING HANDLES**  
easily adjust for  
compact storage and  
allow for one-person  
maneuverability on  
location

**LOCKABLE STORAGE  
CABINET** for cords and  
small tools

**TRANSPORTABLE**  
Fork pockets and lift  
eye; 32 per truckload

# SPECIFICATIONS

Additional options available

LINKTOWER	
<b>Power Source / Outlet</b>	
USA (METRIC)	
Inlet Option A	120V / 15A (NEMA 5-15R) Power Inlet
Inlet Option B	120V / 20A (NEMA L5-20P) Power Inlet
Outlet	120V / 20A (NEMA 5-20R) GFCI Duplex Outlet
<b>Lights &amp; Mast</b>	
Light Fixtures	(4) 235W LED
Total Lumens	122,112
Coverage @ min 0.5ft-c: ft <sup>2</sup> (m <sup>2</sup> )	14,497 (1,347)
Winch	Manual
<b>Weights &amp; Dimensions</b>	
Dimensions, Stowed: in (m)	54 x 31.5 x 77.5 (1.37 x .80 x 1.96 m)
Dimensions, Extended: in (m)	74 x 57 x 192 (1.88 x 1.45 x 4.88)
Weight: lbs (kg)	558 (253)
<b>Ratings &amp; Certifications</b>	
Max. Wind Rating: mph (kph)	45 (72)
dBA	0 (Silent)
LED Modules	IP68
CSA Certified	Yes
<b>Warranty</b>	
2 years on tower / 5 years limited on LED modules and drivers	

# EXTENSION CORD SIZING REQUIREMENTS

## Required To Power One (1) LINKTower

Distance	Cable Size	Plug Ends
50 ft (15.2 m)	12 / 3	L5-20P – L520R
100 ft (30.5 m)	12 / 3	5-15P – 5-15R

Max. Distance	Cable Size	Plug Ends
400 ft (122 m)	10 / 3	L5-20P – L520R
300 ft (91.4 m)	10 / 3	5-15P – 5-15R

## Required To Power Two (2) LINKTowers

Max. Distance - First Unit	Cable Size	Plug Ends
300 ft (91.4 m)	10 / 3	L5-20P – L520R
Max. Distance - Second Unit	Cable Size	Plug Ends
200 ft (61 m)	12 / 3	5-15P – 5-15R



When LINKing two towers, source/input power must be delivered using L5-20P - L5-20R



**Looking for more light?**

Generac Mobile offers powerful, mobile lighting solutions for every need. For our complete line of light towers, visit [GeneracMobileProducts.com](http://GeneracMobileProducts.com).

**24/7 • 365 Nationwide Service Support Network;**  
because when you're on the job, we're on the job.

**GENERAC**<sup>®</sup>  
**MOBILE**