

XC8000E

Specifications

Product Series	XC8000E
Model (Configuration)	6826-0 (EPA/49-State/CSA-Canada) 6827-0 (EPA/CARB-California)
AC Rated Output Running Watts	8000
AC Maximum Output Starting Watts	10000
Rated AC Voltage	120/240 VAC
Rated AC Frequency	60 Hz
Rated 120/240 VAC Amperage	66.6/33.3
Engine Displacement	426cc
Engine Type	Generac G-Force
Engine RPM	3600
Recommended Oil	10W-30 / SAE 30
Lubrication Method	Oil Pump
Automatic Voltage Regulation (AVR)	Yes
Total Harmonic Distortion	<5% (Safe for sensitive electronics)
Choke Location	On Engine
Fuel Shut Off	On Fuel Tank
Starting Method	Electric/Recoil Pull Start
Battery	Included
Battery Type	12VDC
Low Oil Shutdown	Low Pressure
Neutral Bonded to Ground	Yes

Start Switch Type	Start/Run/Stop
Switch Location	On Control Panel
Steel Lifting Pocket	Included
Fuel Gauge	Built-in Tank
Fuel Tank Capacity Gal (Ltrs)	8.5 (32)
Run Time at 50% (Hours)	11
Handle Style	Dual Folding/Locking
Grab Bars	Yes
Wheel Type	10" Solid with Steel Hub
Maintenance Kit	Included
Warranty- Commercial	2 Year Limited
Warranty- Residential	3 Year Limited

Dimensions and Weights

	Model 6826-0	Model 6827-0
Length in (mm)	34.3 (872)	
Width in (mm)	28.6 (727)	
Height in (mm)	32.5 (825)	
Extended Length in (mm)	46.8 (1188)	
Carton Length in (mm)	38.8 (984)	
Carton Width in (mm)	23.5 (597)	
Carton Height in (mm)	30 (762)	
Unit Weight lbs (kg)	260 (117.9)	
Shipping Weight lbs (kg)	280 (127)	

