



YETI 500

**PORTABLE
POWERFUL
RUGGED**



FEATURES

IMPRESSIVE POWER OUTPUT

The Yeti 500 comes with impressive power output for its size! It can run air pumps, Alta portable fridges, and pellet grills and has 500 W AC power out with 1000 W surge abilities.

CLASS-LEADING LIFESPAN

Upgraded LiFePO₄ battery technology gives this little power station a long lifespan. The battery has 4000+ cycles which means you can use it daily for over 10 years.

SUPERIOR FAST CHARGING

Need portable power quickly? Don't worry—the Yeti 500 charges fast! It can recharge from 0% to 100% in less than 90 minutes.

UNRIVALED BUILD QUALITY

The Yeti 500 was built with portability and durability in mind. It passes strict testing to meet UL2743 requirements. It also has an IPX4 rating for water resistance and can handle extreme temperatures.

YETI 500

SKU: #37000
UPC: 847974010082

What's Included:
Yeti 500 - AC Charging Cable

BATTERY:

Cell Chemistry: LiFePO₄ (Lithium Iron Phosphate)
Pack Capacity: 499.2 Wh (25.6 V)
Lifecycles: 4000 (0.5C discharge, climate controlled, 80% original capacity.)
Shelf-life: Charge every 12-18 months (in "main power off" state)
Battery management system: Yes

PORTS:

Output

2x USB-A: 18 W
1x USB-C: 100 W
1x USB-C: 30 W
1x 12V 6mm port: 10 A
1x 12V Car Port: 12 A
2x AC: 500 W, 1000 W Surge
(Combined output of 12 V ports cannot exceed 15 A)

Input

AC Input: 500 W max
8mm Solar: 200 W max

GENERAL:

Chainable: No
Weight (Yeti only): 16.09 lbs (7.3 kg)
Weight (In Box): 19.14 lbs (8.68 kg)
Dimensions (Yeti only): 11.32 x 7.72 x 7.8 in (28.76 x 19.6 x 19.82 cm)
Dimensions (In Box): 13.54 x 9.72 x 10.79 in (34.4 x 24.7 x 27.4 cm)
Operating Usage Temperature:
Charge: 32° to 104°F (0° to 40°C)
Discharge: -4° to 104°F (-20° to 40°C)
Certs:
UL 2743, IEC 62368, UL/IEC 62133, UN 38.3
Limited Warranty: 5 years**

**For warranty terms, conditions, and registration, go to www.goalzero.com/warranty.



*(0.5C discharge, climate controlled, 80% original capacity.)
NOTE: All DC outputs are regulated.