

GPH14M

2- TO 5-TON PACKAGED HEAT PUMPS UP TO 15 SEER & 8.0 HSPF

SUBMITTAL DATA FORM

| Job Name | |
|------------------|---------------|
| | |
| Location | |
| Purchaser | |
| | |
| Order No. | |
| Engineer | |
| Unit No. | |
| Model No. | |
| Model No. | |
| Unit Designation | |
| Performance Data | Certified By: |

Standard Features

- High-efficiency compressor
- Multi-speed ECM blower motor
- Liquid-line filter drier
- Convertible airflow: horizontal or downflow
- All-Aluminum evaporator coil
- Copper tube/aluminum fin condenser coils
- Electric heat kit available as a field-installed option
- AHRI Certified; ETL Listed

Cabinet Features

- Heavy-gauge galvanized-steel cabinet with attractive Architectural Gray powder-paint finish
- Fully insulated air-handling compartment with convenient access panels
- Louvered condenser coil protection
- One footprint; two heights











^{*} Complete warranty details available from your local dealer or at www.goodmanmfg.com. To receive the Lifetime Compressor Limited Warranty (good for as long as you own your home) and the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Québec.

Job Name Location

PERFORMANCE DATA FOR SPLIT SYSTEM

| Cooling Performance | | | |
|------------------------|--|----------|--|
| Total Capacity | | МВН | |
| Sensible Capacity | | MBH | |
| Outdoor Design TMP | | ºF DB/WB | |
| Air Temp entering | | | |
| Evaporator Coil | | ōΕ | |
| Power Input Required | | kW | |
| (less blower motor) | | | |
| Heating Performance | | | |
| Total Heating Capacity | | kW | |
| | | BTU/h | |
| | | | |


| Supply Air Blower Performance | | | |
|-------------------------------|-----------|-----|--|
| Total Supply Air | | CFM | |
| Ext. Static Pressure | - | IWG | |
| Blower Speed | | RPM | |
| Power Output Required | | ВНР | |
| Motor Ratings | - | HP | |
| Power Input Required | | kW | |
| Electr | ical Data | | |
| Power Supply | | | |
| Total Unit Amps | | | |
| Max Overcurrent Device: | | | |
| Fuse Breake | r Amps | | |
| I | | | |

NOTES

2 www.goodmanmfg.com SF-GPH14M

Job Name Location

DIMENSIONS



| MODEL | W" | D" | Н" | CHASSIS SIZE |
|------------|----|----|-----|--------------|
| GPH1424M41 | 47 | 51 | 34¾ | Med. |
| GPH1430M41 | 47 | 51 | 34¾ | Med. |
| GPH1436M41 | 47 | 51 | 34¾ | Med. |
| GPH1442M41 | 47 | 51 | 34¾ | Med. |
| GPH1448M41 | 47 | 51 | 42¾ | Large |
| GPH1460M41 | 47 | 51 | 42¾ | Large |

Job Name Location

ACCESSORIES LIST

| Accessory | ITEM NUMBER | | |
|---|----------------|----------------|---|
| DESCRIPTION | MEDIUM CHASSIS | LARGE CHASSIS | V |
| Concentric Kit | CDK36 | CDK4872 | |
| Downflow Economizer | GPH13MED102 | GPH13MED103 | |
| Downflow Internal Filter Rack | GPH13MFR102 | GPH13MFR103 | |
| Downflow Manual Damper | PGMDD101/102 | PGMDD103 | |
| Downflow Motorized Damper | PGMDMD101/102 | PGMDMD103 | |
| Downflow Square to Round | SQRPG101/102 | SQRPG103 | |
| External Horizontal Filter Rack | GPGHFR101-103 | GPGHFR101-103 | |
| Horizontal Duct Cover | 20464501PDGK | 20464502PDGK | |
| Horizontal Economizer | PEHH101/102 | PEHH103 | |
| Horizontal manual Damper | PGMDH102 | PGMDH103 | |
| Horizontal Motorized Damper | PGMDMH102 | PGMDMH103 | |
| Horizontal Square to Round | SQRPGH101/102 | SQRPGH103 | |
| Outdoor Thermostat & Emergency Heat Relay Kit | OT/EHR18-60 | OT/EHR18-60 | |
| Outdoor Thermostat Kit w/ Lockout Stat | OT18-60A | OT18-60A | |
| Roof Curb | PGC101/102/103 | PGC101/102/103 | |

SINGLE-POINT KIT ACCESSORY KITS

Select the single-point kit accessory based on the unit model.

| Model | SINGLE-POINT KIT |
|--------------|------------------|
| APH1524M41B* | SPK-30 |
| APH1530M41B* | SPK-35 |
| APH1536M41B* | SPK-40 |
| APH1543M41B* | SPK-40 |
| APH1549M41B* | SPK-50 |
| APH1560M41B* | SPK-60 |