



HIGH EFFICIENCY MULTI-ROOM DUCTLESS SYSTEMS



UP TO 5 ZONE



GREE MULTI ZONE



GREE Multi 21 systems, with inverter technology, are some of today's most advanced ductless split heat pumps. Providing both cooling and heating comfort, in as many as five separate zones, they are the perfect solution for many residential and light commercial applications. Multi 21 systems reduce energy waste, maximize efficiency and achieve up to 21 SEER, with our G10 inverter driven compressors. Best of all, the ultimate in reliable room comfort is generated with Eco-friendly R410A refrigerant.

Design Flexibility

Gree introduces project layout flexibility by simultaneously powering up to five indoor units with one outdoor unit. For even greater flexibility, mix and match your choice of Wall Mount, Ceiling Cassette, Concealed Duct, Universal Floor/Ceiling and Mini Floor Console indoor units to create your unique Multi 21 heating and cooling system.

Energy Savings

Gree Multi 21 systems are highly efficient zoning heat pumps that will keep operating costs under control, year round. No need for a bulky add-on coil or expensive-to-operate electric heat. Our variable speed heat pumps, powered by the G10 inverter, provide the same heating capacity as electric heat, while using as little as 1/3 the electricity. With Multi 21 ductless systems, there are no losses due to leaky ductwork.

Maximum Comfort

Multi 21 systems eliminate irritating temperature swings, by continuously monitoring comfort levels and adjusting compressor speed and refrigerant flow according to the cooling and heating needs of each room. Additionally, you can create your own personal-comfort-zone, by activating the I-Feel function on the remote control. With I-Feel activated, Multi 21 systems will sense temperatures surrounding the remote control, and adjust compressor speed and air flow to maintain the comfort level of your personal space.

Durability & Longevity

All duct free Multi 21 units are made from heavy gauge rolled steel and covered with a durable powder coat paint finish. Gree's enhanced Gold-Fin coating provides condenser coil protection in corrosive environments, while improving hydrophilic properties and efficiency; and our multi-point self-diagnostics continuously monitor critical system parameters to prevent catastrophic failures. These, along with many other, design considerations will extend the life of your Multi 21 system.



Multi Zone Inverter Heat Pump



High Efficiency Multi 21 heat pump units can heat and cool up to 5 zones without distribution boxes. Each Multi 21 is powered by Gree's energy efficient G10 inverter and a variable speed compressor. Our G10 inverter technology saves energy, reduces outdoor noise and keeps room temperature steady by eliminating the harsh starts & stops of conventional systems. Each outdoor coil has a corrosion resistant Gold Fin coating to promote energy efficiency and prevent coil corrosion in corrosive environment.



Features and Benefits:

- ▶ High Efficiency up to 21 SEER
- ▶ Sound Levels down to 56 dB(A)
- ▶ Up to 5 indoor units
- ▶ Multi-point Diagnostics
- ▶ Low Ambient Cooling down to 0 deg F
- ▶ Low Ambient Heating down to -4 deg F
- ▶ Intelligent Defrost
- ▶ Heavy Gauge Steel Cabinet
- ▶ R410A Refrigerant

SYSTEM	SIZE		18	24	30	36	42	
	OUTDOOR MODEL		MULTI18HP230V1BO	MULTI24HP230V1BO	MULTI30HP230V1BO	MULTI36HP230V1BO	MULTI42HP230V1BO	
	Max Number of Zones		2	3	4	5	5	
	Energy Star®		YES	NO	YES	YES	NO	
PERFORMANCE NON-DUCTED	Rated Cooling Capacity	Btu/h	18,000	26,000	29,000	34,000	39,000	
	Cooling Cap. Range Min - Max	Btu/h	7,000-21,000	7,500-33,000	8,189-33,438	8,871-35,826	8,871-40,944	
	SEER		22	20.5	21	21	21	
	EER		12.5	9.5	12.0	12.4	10.4	
	Rated Heating Capacity	Btu/h	19,000	29,000	31,600	42,500	45,000	
	Heating Cap. Range Min - Max	Btu/h	8,530-22,600	7,500-35,000	8,189-32,414	8,871-44,356	8,871-46,062	
	HSPF		9	10.2	10.2	10.2	10.2	
	COP	W/W	3.5	3.7	3.8	3.7	3.6	
PERFORMANCE DUCTED	Rated Cooling Capacity	Btu/h	18,000	26,000	29,200	34,000	39,500	
	Cooling Cap. Range Min - Max	Btu/h	7,000-21,000	7,500-33,000	6,200-30,800	13,400-37,000	13,800-42,800	
	SEER		14	14	14.5	14.8	14.7	
	EER		10.9	9.5	9.1	10.1	9.8	
	Rated Heating Capacity	Btu/h	19,000	29,000	32,000	43,500	46,500	
	Heating Cap. Range Min - Max	Btu/h	8,530-22,600	7,500-35,000	6,500-32,500	6,800-13,800	7,500-47,000	
	HSPF		9	9	9.8	9.9	9.6	
	COP	W/W	3.1	3.0	3.29	2.97	3.12	
OPERATING RANGE	Airflow	CFM	1883	2354	2330	4531	4531	
	Sound Pressure	dB(A)	56	59	59	61	61	
OPERATING RANGE	Cooling Outdoor (Min - Max)	°F (oC)	0 ~ 118°F (-18 ~ 48°C)	0 ~ 118°F (-18 ~ 48°C)	0 ~ 118°F (-18 ~ 48°C)	0 ~ 118°F (-18 ~ 48°C)	0 ~ 118°F (-18 ~ 48°C)	
	Heating Outdoor (Min - Max)	°F (oC)	-4 ~ 75°F (-20 ~ 24°C)	-4 ~ 75°F (-20 ~ 24°C)	-4 ~ 75°F (-20 ~ 24°C)	-4 ~ 75°F (-20 ~ 24°C)	-4 ~ 75°F (-20 ~ 24°C)	
PIPING	Total Piping Length	Ft. (m)	65 (20)	197 (60)	230 (70)	246 (75)	246 (75)	
	Piping to furthest Indoor Unit	Ft. (m)	33 (10)	65 (20)	82 (25)	82 (25)	82 (25)	
	Elevation (OD above ID)	Ft. (m)	33 (10)	33 (10)	49 (15)	49 (15)	49 (15)	
	Pipe Connection Size - Gas/Suction ~ Liquid	Port A		1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in
		Port B		1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in
		Port C			1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in
Port D					1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	
Port E						1/4-in ~ 3/8-in	1/4-in ~ 3/8-in	
ELECTRICAL	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60	
	Power Supply		Indoor unit powered from outdoor unit					
	MCA	Amp	15	21	19	21	24	
	MOCP - Fuse Rating	Amp	25	35	30	35	40	
DIMENSIONS & WEIGHT	Unit Width	In.	37.6	38.6	38.6	42.8	42.8	
	Unit Height	In.	27.6	31.1	31.1	43.4	43.4	
	Unit Depth	In.	15.6	16.8	17.3	17.3	17.3	
	Net Weight	lbs.	115/125	153/164	146/154	198/216	198/216	

Premier Wall Mount

Feature-rich with advanced components provide SEER ratings up to 21.0**, the Terra teamed with the Multi-21 is our highest-efficiency indoor high wall model, specially designed to save energy and protect the environment. Sleek and contemporary in appearance, the Terra easily blends in with its surroundings and utilizes a highly intuitive wireless remote control that aids in regulating room temperature with in-built I FEEL automation. Our state-of-the-art Photocatalytic Filter and X-fan improves air quality by eliminating 99.9% of bacteria and viruses, while dually inhibiting mildew growth on its coil.



TERRA
Save energy, protect the environment



(Sold Separately)

Features and Benefits:

- ▶ 4-way Airflow operation (Swing)
- ▶ Waterfall heating airflow
- ▶ 7 Fan Speeds-from Mute to Turbo
- ▶ Photocatalytic Filter
- ▶ I-Feel Automatic Function
- ▶ Optional GREE Tether controller
- ▶ Low voltage start-up
- ▶ Intelligent Pre-heating
- ▶ Comfortable Sleep Mode
- ▶ LED display
- ▶ Self-diagnosis
- ▶ Memory Function

TERRA INDOOR UNIT DATA		TERRA09HP230V1AH	TERRA12HP230V1AH	TERRA18HP230V1BH	TERRA24HP230V1BH
Rated Capacity -Cooling	BtuH	9,000 (3,500~9,600)	12,000 (3,100~13,000)	18,000 (4,600~22,200)	24,000 (2,000~29,300)
-Heating	BtuH	9,800 (2,200~11,000)	13,000 (2,400~14,000)	19,000 (3,400~24,900)	25,000 (2,200~37,500)
Dehumidification	pint/hr	1.9	3.0	3.8	5.3
Power Supply (60hz 1-phase)	volts	208/230V			
Rated Current	amps	0.2	0.2	0.3	0.5
Airflow (min/max)	CFM	118/300	118/312	282/512	294/588
Sound Pressure Level (min/max)	dB(A)	23/38	24/38	33/47	38/49
Unit Dimensions (LxHxW)	inch	34.1 x 11.5 x 8.2	34.1 x 11.5 x 8.2	40.1 x 12.6 x 9.1	46.4 x 12.8 x 10.4
Weight (Net/Gross)	lbs.	24/31	24/31	31/39	39/47
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ1/2	φ1/4 - φ1/2	φ1/4 - φ5/8	φ1/4 - φ5/8
Field Drain Pipe Size O.D.		φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)

** System configurations with 21 SEER ratings: 9K+9K, 9K+9K+12K, 9K+9K+9K+9K and 9K+9K+12K+12K

Tech Series Wall Mount



CROWN



Crown, the ultra-high efficiency smart ductless high wall unit with SEER rating up to 21.0**. This world-class energy efficiency model will lower your utility bills without sacrificing comfort. Slim compact design hangs inconspicuously on the wall and mixes well with most interior designs.

Crown comes with easy-to-use Wireless Remote Controller with an large backlit display. In addition, Crown's built-in Wi-Fi technology allows direct local control from Smartphones with the Gree-Smart application, making it the most convenient choice for today's busy lifestyles.

Features and Benefits:

- ▶ Whisper Quiet down to 26 dB(A)
- ▶ Stainless Platinum Finish
- ▶ I-Feel Temperature Control
- ▶ 180° Multi-Directional Airflow
- ▶ 7 Fan Speeds
- ▶ 4-way Adjustable Swing Louvers
- ▶ Smartphone Interface
- ▶ Intelligent Heating
- ▶ Power Failure Recovery

CROWN INDOOR UNIT DATA		CROWN09HP230V1AH	CROWN12HP230V1AH	CROWN18HP230V1AH
Rated Capacity -Cooling	BtuH	9,000 (1,300~13,600)	12,000 (2,900~15,400)	18,000(4,500~19,200)
-Heating	BtuH	9,000 (2,400~13,600)	13,000 (3,100~18,800)	19,000 (3,753~24,566)
Dehumidification	pint/hr	1.7	3.0	3.8
Power Supply (60hz 1-phase)	volts	208/230V		
Rated Current	amps	0.3	0.3	0.3
Airflow (min/max)	CFM	206/412	265/471	324/530
Sound Pressure Level (min/max)	dB(A)	22/41	23/42	26/48
Unit Dimensions (LxHxW)	inch	37.8 x 12.6 x 8.0	37.8 x 12.6 x 8.0	37.8 x 12.6 x 8.0
Weight (Net/Gross)	lbs.	31/37	31/37	29/35
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ1/2	φ1/4 - φ1/2	φ1/4 - φ5/8
Field Drain Pipe Size O.D.		φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)

** System configurations with 21 SEER ratings: 9K+9K, 9K+9K+12K, 9K+9K+9K+9K and 9K+9K+12K+12K

Comfort Wall Mount

Vireo premium efficiency ductless high wall has a compact design, for quiet comfort and attractive appearance. You can count on consistent comfort from Vireo, which features I-Feel temperature control, multiple fan speeds, and adjustable vertical swing louvers.

The full featured Vireo comes with a multi-functional infrared remote control. It is sleek, easy to use and ergonomically designed with a large LCD display. Vireo is energy efficient, yet powerful enough to keep you comfortable all year round.



(Sold Separately)

Features and Benefits:

- ▶ Four Fan Speeds
- ▶ IR Remote Controller
- ▶ Turbo Mode
- ▶ Vertical Swing Louver
- ▶ Cleanable Air Filter
- ▶ Dry Coil Mode for Anti-Mildew Protection
- ▶ Remote Control Lockout
- ▶ Power Failure Recovery
- ▶ Tether Wired Controller (Optional)

VIREO INDOOR UNIT DATA		VIR09HP230V1AH	VIR12HP230V1AH	VIR18HP230V1AH	VIR24HP230V1AH
Rated Capacity -Cooling	BtuH	9,000 (3,100~9,600)	12,000 (3,100~13,000)	18,000 (6,800~20,000)	22,000 (6,824~27,296)
-Heating	BtuH	11,000 (1,911~12,000)	13,000 (2,400~14,000)	19,800 (7,340~23,500)	23,000 (6,824~30,708)
Dehumidification	pint/hr	1.7	0.2	3.8	4.2
Power Supply (60hz 1-phase)	volts	208/230V			
Rated Current	amps	0.2	0.2	0.3	0.5
Airflow (min/max)	CFM	171/377	171/400	335/559	530/706
Sound Pressure Level (min/max)	dB(A)	29/43	29/45	39/47	36/48
Unit Dimensions (LxHxW)	inch	33.4 x 11.4 x 8.2	33.4 x 11.4 x 8.2	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.7
Weight (Net/Gross)	lbs.	22/26	22/27	29/35	34/42
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ3/8	φ1/4 - φ1/2	φ1/4 - φ5/8	φ1/4 - φ5/8
Field Drain Pipe Size O.D.		φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)	φ5/8-in (φ15-mm)

Ceiling Cassette

Gree's Multi 21 Ceiling Cassette will inconspicuously provide quiet performance through innovative design. The Multi 21 Ceiling Cassette is extremely suitable for any room, and can be easily installed in suspended ceilings with only a discreet decorative discharge grille visible. Gree's fan technology quietly and evenly distributes conditioned air throughout the room, and an internal condensate pump reliably disposes condensate water to a safe location. The Multi 21 Ceiling Cassette is ideal for light commercial applications which require comfort control in large, open spaces. Each Multi 21 Ceiling Cassette can be operated by an infrared remote control or wired tether controller, allowing maximum flexibility for any application.



Features and Benefits:

- ▶ 4-way Discharge Air
- ▶ Multi Speed Fan
- ▶ Remote Control Lockout
- ▶ Swing Louver
- ▶ Decorative Discharge Air Grille (sold separately)
- ▶ IR Remote Control and Tether Wired Controller
- ▶ Power Failure Recovery
- ▶ Internal Condensate Drain Pump
- ▶ Sentry Float Switch
- ▶ Cleanable Air Filter
- ▶ Fresh Air Intake (24K model only)

CEILING CASSETTE INDOOR DATA		CAS12HP230V1AC	CAS18HP230V1AC	CAS24HP230V1AC
Rated Capacity -Cooling	BtuH	12,000	14,400	22,800
-Heating	BtuH	13,000	16,000	27,400
Dehumidification	pint/hr	3.0	3.8	5.2
Power Supply (60hz 1-phase)	volts	208/230V		
Rated Current	amps	0.18	0.18	0.43
Airflow (min/max)	CFM	265/353	265/353	500/694
Sound Pressure Level (min/max)	dB(A)	42/46	42/46	45/49
Unit Dimensions (LxHxW)	inch	22.5 x 9.0 x 22.5	22.5 x 9.0 x 22.5	33.1 x 9.5 x 33.1
Weight (Net/Gross)	lbs.	40/51	40/51	62/78
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ3/8	φ1/4 - φ1/2	φ3/8 - φ5/8
Field Drain Pipe Size O.D.		φ1.2-in (φ31-mm)	φ1.2-in (φ31-mm)	φ1.2-in (φ31-mm)
Decorative Discharge Grilles				
Part Number		CASGRILLE1SM	CASGRILLE1SM	CASGRILLE1LG
Unit Dimensions (LxHxW)	inch	25.6 x 2.0 x 25.6	25.6 x 2.0 x 25.6	37.4 x 2.4 x 37.4
Weight (Net/Gross)	lbs.	6/8	6/8	7/10

Slim Duct

Compact and powerful, the Gree Multi+ Concealed Duct indoor units offer the ultimate in flexibility and discretion. These slim indoor units are designed to be concealed above suspended ceilings or within open closet spaces to deliver conditioned air via ducting and suitable ceiling or wall grilles. This arrangement provides immense flexibility, in terms of both the distribution of conditioned air and the type of grille or diffuser that best compliments the room's styling. Each unit comes with an easy to operate wall mounted tether controller.



Features and Benefits:

- ▶ Medium Static Pressure Capability
- ▶ Slim Line Construction 7-7/8" high
- ▶ Flexible Return Air From Bottom Or Rear
- ▶ Internal Condensate Drain Pump
- ▶ Sentry Float Switch
- ▶ Environmentally Safe R-410A Refrigerant

CONCEALED DUCT INDOOR DATA		DUCT09HP230V1AD	DUCT12HP230V1AD	DUCT18HP230V1AD	DUCT24HP230V1AD
Rated Capacity -Cooling	BtuH	8,500	11,900	15,300	23,800
-Heating	BtuH	9,500	13,100	18,700	27,400
Dehumidification	pint/hr	1.7	3.0	3.8	5.3
Power Supply (60hz 1-phase)	volts	208/230V			
Rated Current	amps	0.28	0.31	0.41	0.5
Airflow (min/max)	CFM	147/265	177/324	294/412	324/589
Sound Pressure Level (min/max)	dB(A)	31/37	32/39	33/41	34/42
Unit Dimensions (LxHxW)	inch	27.6 x 7.9 x 24.2	27.6 x 7.9 x 24.2	35.4 x 7.9 x 24.2	43.3 x 7.9 x 24.2
Weight (Net/Gross)	lbs.	49/60	51/64	60/79	68/90
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ3/8	φ1/4 - φ3/8	φ1/4 - φ1/2	φ3/8 - φ5/8
Field Drain Pipe Size O.D.		φ1.0-in (φ26-mm)	φ1.0-in (φ26-mm)	φ1.0-in (φ26-mm)	φ1.0-in (φ26-mm)

Universal Floor/ Ceiling

Our Multi+ Universal Floor/Ceiling indoor units are designed to be suspended from a ceiling or mounted low on a wall. The slender and lightweight design is perfect for restaurants or hallways where wall space is limited. Aesthetically pleasing to the eye, the Multi+ Universal Floor/Ceiling units are a great fit beneath windows, in public or light commercial applications. Each unit can be operated by an infrared remote control or wired tether controller to allow maximum flexibility in any application.



Features and Benefits:

- ▶ 4-way Discharge Air
- ▶ Multi Speed Fan
- ▶ IR Remote Control and Tether Wired Controller
- ▶ Comfortable Sleep Mode
- ▶ Swing Louver
- ▶ Cleanable Air Filter
- ▶ Dry Coil mode for Anti -Mildew Protection
- ▶ Remote Control Lockout
- ▶ Power Failure Recovery

FLOOR/CEILING INDOOR DATA		FLR09HP230V1AF	FLR12HP230V1AF	FLR18HP230V1AF	FLR24HP230V1AF
Rated Capacity -Cooling	BtuH	8,500	11,900	17,000	22,800
-Heating	BtuH	9,500	13,100	18,700	27,400
Dehumidification	pint/hr	1.7	3.0	3.8	5.3
Power Supply (60hz 1-phase)	volts	208/230V			
Rated Current	amps	0.3	0.3	0.5	0.5
Airflow (min/max)	CFM	265/383	265/383	294/559	412/736
Sound Pressure Level (min/max)	dB(A)	36/40	36/40	40/45	44/48
Unit Dimensions (LxHxW)	inch	48.0 x 27.6 x 8.9	48.0 x 27.6 x 8.9	48.0 x 27.6 x 8.9	48.0 x 27.6 x 8.9
Weight (Net/Gross)	lbs.	88/110	88/110	88/110	100/120
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ3/8	φ1/4 - φ3/8	φ1/4 - φ1/2	φ3/8 - φ5/8
Field Drain Pipe Size O.D.		φ0.67-in (φ17-mm)	φ0.67-in (φ17-mm)	φ0.67-in (φ17-mm)	φ0.67-in (φ17-mm)

Mini Floor Console

Gree's Multi 21 Mini Console indoor units are aesthetically pleasing and the perfect size for any room. The space saving design provides energy efficient solutions for difficult areas that may not have abundant space on the ceiling or walls. It can be mounted as low as six inches above the floor and has front panel access to the filter for ease of cleaning. Each Multi 21 Mini Console unit can be operated by an infrared remote control.



- ▶ 4-way Discharge Air
- ▶ Multi Speed Fan
- ▶ Comfortable Sleep Mode
- ▶ Swing Louver
- ▶ Cleanable Air Filter
- ▶ Dry Coil Mode for Anti-Mildew Protection
- ▶ Environmentally Safe R-410A Refrigerant

MINI-FLOOR CONSOLE INDOOR DATA		CONS09HP230V1AF	CONS12HP230V1AF	CONS18HP230V1AF
Rated Capacity -Cooling	BtuH	9,000	12,000	18,000
-Heating	BtuH	9,500	13,000	19,800
Dehumidification	pint/hr	1.7	3.0	3.8
Power Supply (60hz 1-phase)	volts	208/230V		
Rated Current	amps	0.25	0.25	0.25
Airflow (min/max)	CFM	188/382	206/441	241/494
Sound Pressure Level (min/max)	dB(A)	25/40	27/43	33/48
Unit Dimensions (LxHxW)	inch	27.6 x 23.6 x 8.5	27.6 x 23.6 x 8.5	27.6 x 23.6 x 8.5
Weight (Net/Gross)	lbs.	30/40	30/40	30/40
Refrigerant Port Size (Liquid - Gas/Suction)	inch	φ1/4 - φ3/8	φ1/4 - φ3/8	φ1/4 - φ1/2
Field Drain Pipe Size O.D.		φ1.1-in (φ28-mm)	φ1.1-in (φ28-mm)	φ1.1-in (φ28-mm)



Gree Multi 21 duct free split systems are designed to provide comfort, uncompromising personal style, quiet operation and installation flexibility. Simply choose the type of indoor unit and capacity for each room, and then select your system from our matching outdoor/indoor unit combinations chart (below). For a complete list of matching combinations and capacities, please refer to www.greecomfort.com or check with your GREE dealer/installer.

Matching combinations and capacities:

MULTI18HP230V1BO 2 COMBINATIONS



TWO UNITS
9 + 9
9 + 12

MULTI24HP230V1BO 11 COMBINATIONS



TWO UNITS		THREE UNITS	
9 + 9	12 + 12	9 + 9 + 9	9 + 12 + 12
9 + 12	12 + 18	9 + 9 + 12	12 + 12 + 12
9 + 18	18 + 18	9 + 9 + 18	

MULTI30HP230V1BO 20 COMBINATIONS



TWO UNITS		THREE UNITS		FOUR UNITS
9 + 9	12 + 18	9 + 9 + 9	9 + 12 + 12	9 + 9 + 9 + 9
9 + 12	12 + 24	9 + 9 + 12	9 + 12 + 18	9 + 9 + 9 + 12
9 + 18	18 + 18	9 + 9 + 18	12 + 12 + 12	9 + 9 + 12 + 12
9 + 24	18 + 24	9 + 9 + 24	12 + 12 + 18	
12 + 12				

MULTI36HP230V1BO 31 COMBINATIONS



TWO UNITS		THREE UNITS		FOUR UNITS	FIVE UNITS
9 + 9	12 + 18	9 + 9 + 9	9 + 12 + 24	9 + 9 + 9 + 9	9 + 9 + 9 + 9 + 9
9 + 12	12 + 24	9 + 9 + 12	9 + 18 + 18	9 + 9 + 9 + 12	9 + 9 + 9 + 9 + 12
9 + 18	18 + 18	9 + 9 + 18	12 + 12 + 12	9 + 9 + 9 + 18	
9 + 24	18 + 24	9 + 9 + 24	12 + 12 + 18	9 + 9 + 12 + 12	
12 + 12	24 + 24	9 + 12 + 12	12 + 12 + 24	9 + 9 + 12 + 18	
		9 + 12 + 18	12 + 18 + 18	9 + 12 + 12 + 12	
				9 + 12 + 12 + 18	
				12 + 12 + 12 + 12	

MULTI42HP230V1BO 32 COMBINATIONS



TWO UNITS		THREE UNITS		FOUR UNITS	FIVE UNITS
9 + 9	12 + 18	9 + 9 + 9	9 + 12 + 24	9 + 9 + 9 + 9	9 + 9 + 9 + 9 + 9
9 + 12	12 + 24	9 + 9 + 12	9 + 18 + 18	9 + 9 + 9 + 12	9 + 9 + 9 + 9 + 12
9 + 18	18 + 18	9 + 9 + 18	12 + 12 + 12	9 + 9 + 9 + 18	
9 + 24	18 + 24	9 + 9 + 24	12 + 12 + 18	9 + 9 + 12 + 12	
12 + 12	24 + 24	9 + 12 + 12	12 + 12 + 24	9 + 9 + 12 + 18	
		9 + 12 + 18	12 + 18 + 18	9 + 12 + 12 + 12	
				9 + 12 + 12 + 18	
				12 + 12 + 12 + 12	

Note: It is critical to size the outdoor unit for the entire building load and each indoor unit for its individual zone load.



A company founded on quality and value

GREE Electric Appliances, Inc. is the world's largest specialized air conditioner manufacturer, selling more than 100 million units in over 100 countries since 1991. The GREE brand is world-renowned for engineering 7,000 different models in 20 product categories, developing 3,000 worldwide technical patents and pioneering the Variable Refrigerant Flow system that has revolutionized modern day comfort.

GREE prides itself on the reliability and quality of its products. World class, state-of-the-art quality control methods are employed throughout the manufacturing process, including the use of a separate plant where all key components are pre-tested. More than 1,000 Research & Development technicians spend each day pursuing new and innovative designs as a commitment to ensuring customers always receive the highest quality for the best value in the world.

Scan to learn more about GREE
Inverter ductless system



or visit us at greecomfort.com

Test conditions are based on AHRI 210/240. Specifications are subject to change without notice. Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations. ©2016. All rights reserved. WAT0109-16-v2