

New **Honda Portables** **BF4/5/6**

Best-In-Class Portable Outboard



✓ Decompression function for easy starting, plus a one touch stop button prevents re-starting.



✓ New motor mounts for low vibration and noise



✓ Large internal fuel tank with an external fuel connector (Connector on BF5/6)

✓ Optional 6 Amp charging



✓ Oil alert & RPM reduction for increased protection

Choose **Honda** For Your Best Boating Experience

Engine Specifications

Engine Type	4 stroke, Single Cyl.
Displacement	127cc (7.75 ci)
Bore x Stroke (mm)	60 x 45
Compression Ratio	9.8
Wide Open Throttle Engine Speed Range	(4hp) 4500-5500 (5,6hp) 5000-6000
Rated Power [kW(PS)/rpm]	4hp (2.9 kW) 5000 5hp (3.7 kW) 5500 6hp (4.4 kW) 6000
Fuel Delivery	Carburetor
Driven Valve System	OHV
Lubrication System	Wet Sump

Drive System

Gear Ratio	2.08:1
Gear Shift	F-N-R

Mounting System

Tilt Angle	70°
Trim Angle	16°
Trim Adjustment Range	4° (5 Hole)
Steering Angle	45° (One Side)

Dimensions

Transome Type(in)Overall Length (mm)	S (15) L (20) 524
Overall Width (mm)	347
Overall Height (mm)	S 1020 L 1147
Transom Height (mm)	S 434 L 561
Dry Mass (lbs, kg)	S 59.5 lbs (27kg) L 60.6 lbs (27.5kg)

Equipment

Starting System	Recoil Starter
Alternator (Charging)	12V 6A (opt.)
Ignition System	Digital CDI
Tilt System	Mechanical
Built-In Tank Capacity	1.5 L
Propeller	7 7/8" x 7 1/2"
Optional Propellers	3 Models Available
Lockable Clamps	Standard
Throttle Friction	Standard
4-Front Paint Process	Standard

In developing this new portable series, the Honda R & D team conducted hundreds of test sessions in order to provide a complete performance package for more comfortable journeys and to ensure the highest reliability when conditions are the worst.

Whatever your needs, there is a right sized Honda for the right purpose.

Easy to Start & Stop

The *decompression mechanism* opens the exhaust valve during the starting process, making it so easy to start. Pressing the stop button once safely shuts off the motor without it re-starting.

Internal Fuel Tank

The **1.5L** internal tank provides enough fuel for **over 40 minutes of wide open throttle** operation. If that's not enough, the BF5 and BF6 offer an external fuel tank connection.

Quiet & Smooth

Newly designed motor mounts reduce engine noise and vibration to your hand.



6 Amps of Charging

Available as a dealer-installed option. A 6 Amp charging system helps keep accessories and electronics charged.

Ergonomics

Enlarged carrying handles ensure a positive grip when transporting. The tiller handle folds down for easy storing.



Double Alerts

A *low oil alert* combined with an *RPM reduction* feature protects the engine and increases reliability.

HONDA

MARINE