

30 Gallon Cast Iron - Oil Lubricated - Belt Drive

FEATURES & BENEFITS

- Cast iron, twin cylinder, oil lubricated pump features
 - One-piece cast iron crankcase
 - Thermally stable cast iron cylinder body
 - Aluminum head & valve plate
 - Automotive style ball bearings
 - Durable Swedish stainless steel reed valves
 - Oil level sight glass
 - Easily accessible oil fill
 - 12" cast iron balanced flywheel
- Heavy duty induction motor for maximum performance and efficiency
- 155 PSI max pressure for optimum tool performance
- 30 gallon ASME* vertical portable tank with pre-attached pneumatic tires for maximum portability
- Dual voltage motor is wired for standard 120 volt outlet, and may also be converted for 240 volt application
- Shipped with synthetic oil for optimum performance and long life
- Equipped with quick-set regulator, tank and working pressure gauges, and on/off switch
- Supported by our Toll Free Customer Help Line



MODEL SPECIFICATIONS

Tank Size:	30 Gallon ASME*
Maximum Pressure:	155 PSI
CFM @ 40 PSI:	7.0
CFM @ 90 PSI:	5.7
Voltage:	120/240 Volt
Running HP:	1.9
Certifications:	UL & CSA
Warranty:	2 Year Limited

Dimensions: 24.25" x 29.25" x 48.5" • Weight: 190 lbs. • UPC: 8 46212 00155 4 • Pallet Qty: 4 • Truckload Qty: 192 (53' trailer)

*ASME - American Society of Mechanical Engineers Product style and configuration may vary.



MODEL: ILA1883054