


ENGINE TYPE	Forced Air-Cooled V-twin 4-cycle Vertical Shaft OHV Gasoline Engine
Number of Cylinders	2
Bore x Stroke	2.9 x 2.8 in. (73 x 72mm)
Displacement	603cc (36.8 cu. in.)
Compression Ratio	8.1:1
Maximum Power	15.0hp (11.2kW) / 3600 rpm
Maximum Torque	31.0 ft. lbs. (42.1 N•m) / 1800 rpm
Oil Capacity	1.8 U.S. qt. (1.7 liter) w/Filter
Dry Weight (without muffler)	80.9 lbs. (36.7kg)

- 90° V-twin
- Pressurized lubrication system
- Electronic spark ignition
- Automatic compression release
- Dual element air filter
- Cast-iron cylinder liners
- Rotating metal grass chopper screen



FS541V / 15.0 HP




**CRITICAL
POWER**

FS600V / 18.5 HP



ENGINE TYPE	Forced Air-Cooled V-twin 4-cycle Vertical Shaft OHV Gasoline Engine
Number of Cylinders	2
Bore x Stroke	2.9 x 2.8 in. (73 x 72mm)
Displacement	603cc (36.8 cu. in.)
Compression Ratio	8.1:1
Maximum Power	18.5hp (13.8kW) / 3600 rpm
Maximum Torque	32.5 ft. lbs. (44.1 N•m) / 2000 rpm
Oil Capacity	1.8 U.S. qt. (1.7 liter) w/Filter
Dry Weight (without muffler)	80.9 lbs. (36.7kg)

- 90° V-twin
- Pressurized lubrication system
- Electronic spark ignition
- Automatic compression release
- Dual element air filter
- Cast-iron cylinder liners
- Rotating metal grass chopper screen



**CRITICAL
POWER**