



1/6 hp utility pump, 115 V, 10' cord, manual operation

Item: 505723

Model: Next Gen 5-MSP 10-Ft Cord

Ratings

| | |
|-----------------------------|--------------------|
| Frequency | 60 Hz |
| Phase | Single-Phase |
| Amps - Full Load | 5 A |
| Amps - Starting | 6.4 A |
| Full Load Watts | 380 W |
| Volts | 115 VAC |
| Cord Length | 10 ft |
| Lead Length | 10 ft |
| Motor Type | Submersible |
| Continuous Duty | Yes |
| Thermal Overload Protection | Yes |
| Protection [IP] | IP68 |
| Maximum Flow Rate - 60Hz | 25 gpm / 1500 gph |
| Minimum Flow Rate - 60Hz | 4.17 gpm / 250 gph |
| Shut-Off | 26 ft |
| Minimum Head - 60Hz | 1.31 ft |
| Shut Off Height - 60Hz | 26.3 ft |
| Stages | 1 |
| Max Solid Handling Size | 0.13 " |
| Switch Type | Manual |
| Motor Cooling | Water |

Liquid

| | |
|-----------------------|--------|
| Max Fluid Temperature | 120 °F |
|-----------------------|--------|

Materials of Construction

| | |
|----------------------------|-----------------|
| Pump Base Material | Plastic |
| Pump Body Material | Aluminum |
| Pump Volute Material | Nylon |
| Impeller Type | Semi-open |
| Impeller Material | Nylon |
| Motor Shaft End - Material | Stainless Steel |
| Intake Screen Material | Nylon |
| Top Bearing Type | Sleeve |
| Bottom Bearing Type | Sleeve Bearing |
| Seal Material | Viton Retainer |
| Seal Type | Viton |

Installation

| | |
|------------------------|-----------------|
| Discharge Thread | FNPT |
| Discharge Type | Threaded - FNPT |
| Discharge | 1 " |
| Product Length | 6.1 " |
| Product Width | 4.29 " |
| Product Height | 8.07 " |
| Pump Length | 6.1 " |
| Product Weight | 6.92 lb |
| Product Weight w/ Pack | 7.42 lb |
| Carton Length | 7.28 " |
| Carton Width | 5.51 " |
| Carton Height | 9.45 " |

Other

| | |
|-----------------------------|------------------------------|
| Accessories Included | 3/4" GHT garden hose adapter |
| Electrical Agency Approvals | UL |
| Standard Warranty | 12 Months |

[Warranty Terms and Conditions Link](#)